

Interchange Databases

Table of Contents

<u>1. Interchange Databases</u>	<u>1</u>
<u>1.1. A Typical User Session</u>	<u>1</u>
<u>2. Databases</u>	<u>3</u>
<u>2.1. Text Source Files</u>	<u>3</u>
<u>2.2. Interchange Database Operation</u>	<u>4</u>
<u>2.3. The Product Database</u>	<u>6</u>
<u>2.4. Multiple Database Tables</u>	<u>7</u>
<u>2.5. Character Usage Restrictions</u>	<u>8</u>
<u>2.6. Database Attributes</u>	<u>9</u>
<u>2.7. Dictionary Indexing With INDEX</u>	<u>11</u>
<u>2.8. MEMORY for Memory-Only Databases</u>	<u>12</u>
<u>2.9. IMPORT ONCE</u>	<u>12</u>
<u>2.10. Importing in a Page</u>	<u>12</u>
<u>2.11. Exporting from a Database</u>	<u>13</u>
<u>2.12. Write Control</u>	<u>13</u>
<u>2.13. Global Databases</u>	<u>14</u>
<u>3. SQL Support</u>	<u>15</u>
<u>3.1. SQL Support via DBI</u>	<u>15</u>
<u>3.2. SQL Access Methods</u>	<u>17</u>
<u>3.3. Importing from an ASCII File</u>	<u>17</u>
<u>4. The Search Engine</u>	<u>19</u>
<u>4.1. The Search Form</u>	<u>19</u>
<u>4.2. Glimpse</u>	<u>20</u>
<u>4.3. Fast Binary Search</u>	<u>21</u>
<u>4.4. Coordinated and Joined Searching</u>	<u>22</u>
<u>4.5. Specifying a Text-Based Search with SQL-Like Syntax</u>	<u>24</u>
<u>4.6. Range Searching</u>	<u>25</u>
<u>4.7. One-Click Searches</u>	<u>25</u>
<u>4.8. Setting Display Options with mv_value</u>	<u>28</u>
<u>4.9. In-Page Searches</u>	<u>28</u>
<u>4.10. Search Profiles</u>	<u>29</u>
<u>4.11. Search Reference</u>	<u>30</u>
<u>4.12. The Results Page</u>	<u>37</u>
<u>5. Sorting</u>	<u>43</u>
<u>6. Shipping</u>	<u>47</u>
<u>6.1. Shipping Cost Database</u>	<u>47</u>
<u>6.2. Criteria Determination</u>	<u>49</u>
<u>6.3. Shipping Calculation Modes</u>	<u>50</u>
<u>6.4. How Shipping is Calculated</u>	<u>51</u>
<u>6.5. More On UPS-Style Lookup</u>	<u>53</u>
<u>6.6. Geographic Qualification</u>	<u>55</u>
<u>6.7. Handling Charges</u>	<u>55</u>

Table of Contents

6.8. Default Shipping Mode	56
7. User Database	57
7.1. The [userdb ...] Tag	58
7.2. Setting Defaults with the UserDB Directive	60
7.3. User Database Functions	61
7.4. Address Book	64
7.5. Accounts Book	65
7.6. Preferences	66
7.7. Carts	66
7.8. Controlling Page Access With UserDB	66
8. Back Office UI	69
8.1. [display] tag and mv_metadata	69
9. Standard Database Dictionary	71
9.1. 2ndDayAir.csv	71
9.2. 450.csv	71
9.3. Ground.csv	71
9.4. NextDayAir.csv	71
9.5. access.asc	71
9.6. affiliate.txt	72
9.7. area.txt	72
9.8. banner.txt	72
9.9. cat.txt	73
9.10. component.txt	73
9.11. country.txt	73
9.12. downloadable.txt	74
9.13. files.txt	74
9.14. gift_certs.txt	74
9.15. icmenu.txt	74
9.16. inventory.txt	74
9.17. locale.txt	75
9.18. merchandising.txt	75
9.19. mv_metadata.asc	75
9.20. options.txt	76
9.21. order_returns.txt	77
9.22. orderline.txt	77
9.23. pricing.txt	78
9.24. products.txt	78
9.25. route.txt	79
9.26. saletax.asc	79
9.27. shipping.asc	79
9.28. state.txt	79
9.29. transactions.txt	80
9.30. userdb.txt	81
9.31. variable.txt	82

Table of Contents

<u>10. Frequently Asked Questions.....</u>	<u>83</u>
<u>10.1. Does Interchange require an SQL database?.....</u>	<u>83</u>
<u>10.2. I can't get SQL to work: Undefined subroutine &Vend::Table::DBI::create</u>	<u>83</u>
<u>10.3. How can I use Interchange with Microsoft Access?.....</u>	<u>84</u>
<u>11. Interchange Database Usertags.....</u>	<u>87</u>
<u>11.1. Data.....</u>	<u>87</u>
<u>11.2. db_date.....</u>	<u>88</u>
<u>11.3. search_region.....</u>	<u>88</u>

1. Interchange Databases

Interchange is the industry's most widely distributed and implemented open source e-commerce platform. This document discusses databases, SQL support, the Interchange search engine, frequently asked questions, and usertags.

1.1. A Typical User Session

The customer discovers a merchant site using the Interchange catalog with a search engine, a link from another page, or a click-through from a banner ad. He or she clicks the link, which is a URL pointing to the Interchange CGI link program (generically called VLINK or TLINK). The link calls the Interchange server through a socket. The Interchange server detects the path information from the link, and loads the corresponding page.

The displayed page contains links to either locate or order items from the merchant's catalog. When the customer clicks a link to purchase an item, Interchange searches the product database, finds the item, and places it in the customer's shopping cart. (Each user has a separate shopping cart, which is attached to their session.)

Once the customer decides to purchase the items in their shopping cart, he or she checks out by completing a form with their name, address, payment information, shipping information, and any other information that may be required. Interchange has the capacity to compute sales taxes and shipping cost. The order is then submitted. The customer's payment can be taken online by real-time electronic payment, or their order information may be transmitted using encrypted email or FAX to a processing center.

The customer's order is saved to a file or to a database table as backup. In the case of fully automated systems, it can be sent directly to an order entry program or database link.

All of these operations are fully configurable. The Interchange demo program includes a sample store called Construct Something. Some users have actually customized the text and images inside Construct Something's sample catalogs, changed the database entries, and opened their store. Most users, however, have built their catalogs using their own distinctive look and feel.

2. Databases

As with most powerful shopping cart programs, Interchange is all about databases. Interchange can use GDBM, DB_File, SQL, LDAP, or in-memory database formats. In most cases, these different database formats should operate the same when called by Interchange's access methods.

Note: No other database besides Interchange's internal one is required.

Keeping a database in an SQL manager makes it easier to integrate Interchange with other tools. Interchange can be used to maintain a spreadsheet containing product information by only modifying the file `products.txt` as needed. References to SQL, DBI, and DBD can be ignored.

2.1. Text Source Files

Interchange reads delimited text files to obtain data. However, the text files are not the database. They are the source information for the database tables.

Note the following configuration directive:

```
Database products products.txt TAB
```

This says that the `products` table will obtain its source information from the file `products.txt`. What is done with it depends on the type of underlying database being used. The different types:

GDBM

The database source file is checked to see if it is newer than the actual database file, which would be `products.gdbm`. If it is, then the database table is re-imported from the file.

This behavior can be changed in a couple of ways. If files are never to be imported unless the `.gdbm` file disappears, set the `NoImport` directive:

```
NoImport products
```

If the database source file is only imported at catalog start-up time, use the `IMPORT_ONCE` modifier:

```
Database products IMPORT_ONCE 1
```

GDBM is the default type if the GDBM_File Perl module is installed (as it will be on LINUX).

DB_File

The database source file is checked to see if it is newer than the actual database file, which would be `products.db`. If it is, then the database table is re-imported from the file. You can change this behavior in the same way as with GDBM_File (above).

DB_File is the default type if the GDBM_File Perl module is not installed. This is typical on FreeBSD. To explicitly specify DB_File as the type, specify it with a Database directive in `catalog.cfg`:

```
Database products DB_FILE 1
```

DBI/SQL

If a file named `products.sql` is present in the same directory as `products.txt`, the database table will not be imported from ASCII source. If there is no `products.sql`, the following will occur:

DBI/SQL imports only happen at catalog configuration time.

Interchange will connect to the SQL database using the specified DSN. (DBI parameter meaning "Database Source Name".)

The table will be dropped with "DROP TABLE products;". This will occur without warning! NOTE: This can be prevented in several ways. See `NoImport External` or the SQL documentation.

The table will be created. If there are `COLUMN_DEF` specifications in `catalog.cfg`, they will be used. Otherwise, the key (first field in the text file by default) will be created with a `char(16)` type and all other fields will be created as `char(128)`. The table creation statement will be written to the `error.log` file. The text source file will be imported into the SQL database. Interchange will place the data in the columns. Data typing must be user-configured. This means that if "none" is placed in a field, and it is defined as a numeric type, the database import will not succeed. If it does not, the catalog will not become active.

In-Memory

Every time the catalog is configured, the `products.txt` file is imported into memory and forms the database. The database is not changed otherwise. In-memory is the default type if there is no `GDBM_File` or `DB_File` Perl module installed; specify it with:

```
Database    products    MEMORY    1
```

2.2. Interchange Database Operation

Note: In the following descriptions, the following terms are used somewhat interchangeably:

key, code

Either one is a reference to the key for the database. In Interchange, this is often the product code or SKU, which is the part number for the product. Other key values may be used to generate relationships to other database tables.

It is suggested that the key be the first column of the ASCII source file, since Interchange's import, export, and search facilities will work much better with that practice.

field, column

This is a column of the database. One of the columns is always the key; Interchange prefers that the key be the first column.

table, database

A table in the database. Because of the evolution of Interchange from a single-table database to an access method for an unlimited number of tables (and databases, for that matter), a table will sometimes be referred to as a database. The only time database refers to something different is when describing that concept as it

Interchange Databases

relates to SQL, where a database contains a series of tables. Interchange cannot create SQL databases, but given the proper permissions it may drop and create tables within that database.

If necessary, Interchange reads the data to place in tables from standard ASCII–delimited files. All of these ASCII source files are kept in the products directory, normally products in the catalog directory (where catalog.cfg is located). The ASCII files can have ^M (carriage return) characters if desired, but must have a new line character at the end of the line to work. NOTE: Mac users uploading files must use ASCII mode, not binary mode.

Interchange's default ASCII delimiter is TAB.

Note: The items must be separated by a single delimiter. The items are lined up for reading convenience.

TAB

Fields separated by ^I characters. No whitespace should be at the beginning of the line.

```
code      description          price  image
SH543    Men's fine cotton shirt 14.95  shirts.jpg
```

PIPE

Fields separated by | characters. No whitespace should be at the beginning of the line.

```
code|description|price|image
SH543|Men's fine cotton shirt|14.95|shirts.jpg
```

CSV

Fields enclosed in quotes, separated by commas. No whitespace should be at the beginning of the line.

```
"code","description","price","image"
"SH543","Men's fine cotton shirt","14.95","shirts.jpg"
```

Note: Using the default TAB delimiter is highly recommended, if searching the ASCII source file of the database is planned. PIPE works fairly well, but CSV delimiter schemes cause problems with searching.

IMPORTANT NOTE: Field names are usually case–sensitive. Unless there is consistency in the names, there will be problems. All lower or all upper case names are recommended.

Interchange uses one mandatory database, which is referred to as the products database. In the supplied demo catalogs, it is called products and the ASCII source is kept in the file products.txt in the products directory. This file is also the default file for searching with the THE SEARCH ENGINE.

Interchange also has a two of standard, but optional, databases, which are in fixed special formats:

shipping.asc

The database of shipping options if the `CustomShipping` directive is in use. This is a fixed-format database, and must be created as specified. See `SHIPPING`.

salestax.asc

The database of sales tax information if the `[salestax]` tag is to be used. A default is supplied. NOTE: Caution, these things change! This is a fixed-format database, and must be created as specified. See `Sales Tax`.

These are never stored in SQL or DBM.

2.3. The Product Database

Each product being sold should be given a product code, usually referred to as SKU, a short code that identifies the product on the ordering page and in the catalog. The `products.txt` file is a ASCII-delimited list of all the product codes, along with an arbitrary number of fields which must contain at least the fields `description` and `price` (or however the `PriceField` and `DescriptionField` directives have been set). Any additional information needed in the catalog can be placed in any arbitrary field. See `Interchange Database Capability` for details on the format.

Field names can be case-sensitive depending on the underlying database type. Unless there are fields with the names "description" and "price" field, set the `PriceField` and `DescriptionField` directives to use the `[item-price]` and `[item-description]` tags.

The product code, or SKU, must be the first field in the line, and must be unique. Product codes can contain the characters **A–Za–z0–9**, along with hyphen (-), underscore (_), pound sign/hash mark (#), slash (/), and period (.). Note that slash (/) will interfere with on-the-fly page references. Avoid if at all possible.

The words should be separated by one of the approved delimiting schemes (TAB, PIPE, or CSV), and are case-sensitive in some cases. If the case of the "description" or "price" fields have been modified, the `PriceField` and `DescriptionField` directives must be appropriately set.

Note: CSV is not recommended as the scheme for the products database. It is much slower than TAB- or PIPE-delimited, and dramatically reduces search engine functionality. No field-specific searches are possible. Using CSV for any small database that will not be searched is fine.

IMPORTANT NOTE: The field names must be on the first line of the `products.txt` file. These field names must match exactly the field names of the `[item-field]` tags in the catalog pages, or the Interchange server will not access them properly. Field names can contain the characters **A–Za–z0–9** and underscore (_).

More than one database may be used as a products database. If the catalog directive, `ProductFiles`, is set to a space-separated list of valid Interchange database identifiers, those databases will be searched (in the order specified) for any items that are ordered, or for product information (as in the `[price code]` and `[field code]` tags).

When the database table source file (i.e., products.txt) changes after import or edit, a DBM database is re-built upon the next user access. No restart of the server is necessary.

If changing the database on-the-fly, it is recommended that the file be locked while it is being modified. Interchange's supplied import routines do this.

2.4. Multiple Database Tables

Interchange can manage an unlimited number of arbitrary database tables. They use the TAB delimiter by default, but several flexible delimiter schemes are available. These are defined by default:

Type 1	DEFAULT - uses default TAB delimiter
Type 2	LINE Each field on its own line, a blank line separates the record. Watch those carriage returns! Also has a special format when CONTINUE is set to be NOTES.
Type 3	%% Fields separated by a \n%%\n combination, records by \n%%%\n (where \n is a newline). Watch those carriage returns!
Type 4	CSV
Type 5	PIPE
Type 6	TAB
Type 7	reserved
Type 8	SQL

The databases are specified in Database directives, as:

```
Database    arbitrary arbitrary.csv CSV
```

This specifies a Type 4 database, the ASCII version of which is located in the file arbitrary.csv, and the identifier it will be accessed under in Interchange is "arbitrary." The DBM file, if any, will be created in the same directory if the ASCII file is newer, or if the DBM file does not exist. The files will be created as arbitrary.db or arbitrary.gdbm, depending on DBM type.

The identifier is case sensitive, and can only contain characters in the class [A-Za-z0-9_]. Fields are accessed with the [item_data identifier field] or [data identifier field key] elements. NOTE: Use of lower-case letters is strongly recommended.

If one of the first six types is specified, the database will automatically be built in the default Interchange DB style. The type can be specified with DB_FILE, GDBM, or MEMORY, if the type varies from that default. They will coexist with an unlimited number of DBI databases of different types.

In addition to the database, the session files will be kept in the default format, and are affected by the following actions.

The order of preference is:

GDBM

This uses the Perl GDBM_File module to build a GDBM database. The following command will indicate if GDBM is in Perl:

Interchange Databases

```
perl -e 'require GDBM_File and print "I have GDBM.\n"'
```

Installing GDBM_File requires rebuilding Perl after obtaining the GNU GDBM package, and is beyond the scope of this document. LINUX will typically have this by default; most other operating systems will need to specifically build in this capability.

DB_File (Berkeley DB)

This uses the DB_File module to build a Berkeley DB (hash) database. The following command will indicate if DB_File is in Perl:

```
perl -e 'require DB_File and print "I have Berkeley DB.\n"'
```

Installing DB_File requires rebuilding Perl after obtaining the Berkeley DB package, and is beyond the scope of this document. BSDI, FreeBSD, and LINUX will typically have it by default; most other operating systems will need to specifically build this in.

If using DB_File, even though GDBM_File is in Perl, set the environment variable MINIVEND_DBFILE to a true (non-zero, non-blank) value:

```
# csh or tcsh
setenv MINIVEND_DBFILE 1

# sh, bash, or ksh
MINIVEND_DBFILE=1 ; export MINIVEND_DBFILE
```

Then, re-start the server.

Or, to set a particular table to use Berkeley DB, the DB_FILE class in catalog.cfg can be specified:

```
Database arbitrary DB_FILE 1
```

In-memory

This uses Perl hashes to store the data directly in memory. Every time the Interchange server is restarted, it will re-import all in-memory databases for every catalog.

If this is used, despite the presence of GDBM_File or DB_File, set the environment variable MINIVEND_NODBM as above or specify the memory type in the Database directive:

```
Database arbitrary MEMORY 1
```

Note: The use of memory databases is not recommended.

2.5. Character Usage Restrictions

To review, database identifiers, field names, and product codes (database keys) are restricted in the characters they may use. The following table shows the restrictions:

	Legal characters

Database identifiers	A-Z a-z 0-9 _
Field names	A-Z a-z 0-9 _

Interchange Databases

Database keys (product code/SKU)	A-Z a-z 0-9 _ # - . /
Database values	Any (subject to field/record delimiter)

Some SQL databases have reserved words which cannot be used as field names; Interchange databases do not have this restriction.

For easy HTML compatibility, it is not recommended that a / be used in a part number if using the flypage capability. It can still be called [page href=flypage arg="S/KU"].

2.6. Database Attributes

Especially in SQL databases, there are certain functions that can be set with additional database attributes. For text import, the CONTINUE extended database import attribute allows additional control over the format of imported text.

Note: CONTINUE applies to all types except CSV. (Do not use NOTES unless using type LINE.)

CONTINUE

One of UNIX, DITTO, LINE, NONE, or NOTES. The default, NONE, is to simply split the line/record according to the delimiter, with no possible spanning of records. Setting CONTINUE to UNIX appends the next line to the current when it encounters a backslash (\) at the end of a record, just like many UNIX commands and shells.

DITTO is invoked when the key field is blank. It adds the contents of following fields to the one above, separated by a new line character. This allows additional text to be added to a field beyond the 255 characters available with most spreadsheets and flat-file databases.

Example in catalog.cfg:

```
Database products products.txt TAB
Database products CONTINUE DITTO
```

Products.asc file:

```
code      price      description
00-0011   500000      The Mona Lisa, one of the worlds great masterpieces.
                                Now at a reduced price!
```

The description for product 00-0011 will contain the contents of the description field on both lines, separated by a new line.

Note: Fields are separated by tabs, formatted for reading convenience.

This will work for multiple fields in the same record. If the field contains any non-empty value, it will be appended.

LINE is a special setting so a multi-line field can be used. Normally, when using the LINE type, there is only data on one line separated by one blank line. When using CONTINUE LINE, there may be some number of fields which are each on a line, while the last one spans multiple lines up until the first blank line.

Interchange Databases

Example in catalog.cfg:

```
Database products products.txt  LINE
Database products CONTINUE      LINE
```

Products.asc file:

```
code
price
description

00-0011
500000
The Mona Lisa, one of the worlds great masterpieces.
Now at a reduced price!

00-0011a
1000
A special frame for the Mona Lisa.
```

NOTES reads a Lotus Notes "structured text" file. The format is any number of fields, all except one of which must have a field name followed by a colon and then the data. There is optional whitespace after the colon.

Records are separated by a settable delimiting character which goes on a line by itself, much like a "here document." By default, it is a form feed (^L) character. The final field begins at the first blank line and continues to the end of the record. This final field is named `notes_field`, unless set as mentioned below. Interchange reads the field names from the first paragraph of the file. The key field should be first, followed by other fields in any order. If one (and only one) field name has whitespace, then its name is used for the `notes_field`. Any characters after a space or TAB are used as the record delimiter.

If there are none, then the delimiter returns to the default form feed (^L) and the field name reverts to `notes_field`. The field in question will be discarded, but a second field with whitespace will cause an import error. Following records are then read by name, and only fields with data in them need be set. Only the `notes_field` may contain a new line. It is always the last field in the record, and begins at the **first** blank line.

The following example sets the delimiter to a tilde (~) and renames the `notes_field` to `description`.

Example in catalog.cfg:

```
Database products products.txt  LINE
Database products CONTINUE      NOTES
```

Products.asc file:

```
code
title
price
image
description ~
size
color

title: Mona Lisa
price: 500000
code: 00-0011
image: 00-0011.jpg

The Mona Lisa, one of the worlds great masterpieces.
```



```
Now at a reduced price!
~
title: The Art Store T-Shirt
code: 99-102
size: Medium, Large*, XL=Extra Large
color: Green, Blue, Red, White*, Black
price: 2000

Extra large 1.00 extra.
~
```

EXCEL

Microsoft Excel is a widely-used tool to maintain Interchange databases, but has several problems with its standard TAB-delimited export, like encasing fields containing commas in quotes, generating extra carriage returns embedded in records, and not including trailing blank fields. To avoid problems, use a text-qualifier of none.

Set the EXCEL attribute to 1 to fix these problems on import:

```
Database products EXCEL 1
```

This is normally used only with TAB-delimited files.

2.7. Dictionary Indexing With INDEX

Interchange will automatically build index files for a fast binary search of an individual field. This type of search is useful for looking up the author of a book based on the beginning of their last name, a book title based on its beginning, or other similar situations.

Such a search requires a dictionary ordered index with the field to be searched contained in the first field and the database key (product code) in the second field. If the INDEX field modifier is specified, Interchange will build the index upon database import:

```
Database products products.txt TAB
Database products INDEX title
```

If the title field is the fourth column in the products database table, a file products.txt.4 will be built, containing two tab-separated fields something like:

```
American Gothic 19-202
Mona Lisa       00-0011
Sunflowers      00-342
The Starry Night 00-343
```

Options can be appended to the field name after a colon (:). The most useful will be f, which does a case-insensitive sort. The mv_dict_fold option must be added to the search in this case.

Another option is c, which stands for "comma index." To index on comma-separated sub-fields within a field, use the :c option:

```
Database products products.txt TAB
Database products INDEX category:c
```

This can get slow for larger databases and fields. Interchange will split the field on a comma (stripping

surrounding whitespace) and make index entries for each one. This allows multiple categories in one field while retaining the fast category search mechanism. It might also be useful for a keywords field.

The fast binary search is described in greater detail in THE SEARCH ENGINE below.

2.8. MEMORY for Memory–Only Databases

Interchange's memory–based databases are the fastest possible way to organize and store frequently used data. To force a database to be built in memory instead of DBM, use the MEMORY modifier:

```
Database country country.asc TAB
Database country MEMORY 1
```

Obviously, large tables will use a great deal of memory, and the data will need to be re–imported from the ASCII source file at every catalog reconfiguration or Interchange restart. The big advantage of using MEMORY is that the database remains open at all times and does not need to be reinitialized at every connect. Use it for smaller tables that will be frequently accessed.

The MEMORY modifier forces IMPORT_ONCE.

2.9. IMPORT_ONCE

The IMPORT_ONCE modifier tells Interchange not to re–import the database from the ASCII file every time it changes. Normally, Interchange does a comparison of the database file modification time with the ASCII source every time it is accessed, and if the ASCII source is newer it will re–import the file.

IMPORT_ONCE tells it only to import on a server restart or catalog reconfiguration:

```
Database products products.txt TAB
Database products IMPORT_ONCE 1
```

SQL databases don't normally need this. They will only be imported once in normal operation. Also see NoImport for a way to guarantee that the table will never be imported.

IMPORT_ONCE is always in effect for MEMORY databases. A catalog reconfiguration is required to force a change.

2.10. Importing in a Page

To add a data record to a database as a result of an order or other operation, use Interchange's [import . . .] tag.

[import table type*] RECORD [/import]

Named parameters:

```
[import table=table_name
file=filename*
type=(TAB|PIPE|CSV|%%|LINE)*
continue=(NOTES|UNIX|DITTO)*
separator=c*]
```

Import one or more records into a database. The `type` is any of the valid Interchange delimiter types, with the default being `TAB`. The table must already be a defined Interchange database table. It cannot be created on-the-fly. If on-the-fly functionality is need, it is time to use `SQL`.

The import type selected need not match the type the database was specified. Different delimiters may be used.

The `type` of `LINE` and `continue` setting of `NOTES` is particularly useful, for it allows fields to be named and not have to be in any particular order of appearance in the database. The following two imports are identical in effect:

```
[import table=orders]
      code: [value mv_order_number]
shipping_mode: [shipping-description]
      status: pending
[/import]

[import table=orders]
shipping_mode: [shipping-description]
status:      pending
code:      [value mv_order_number]
[/import]
```

The `code` or `key` must always be present, and is always named `code`. If `NOTES` mode is not used, the fields must be imported in the same order as they appear in the ASCII source file.

The `file` option overrides the container text and imports directly from a named file based in the catalog directory. To import from `products.txt`, specify `file="products/products.txt"`. If the `NoAbsolute` directive is set to `Yes` in `minivend.cfg`, only relative path names will be allowed.

The `[import] TEXT [/import]` region may contain multiple records. If using `NOTES` mode, a separator must be used, which, by default, is a form-feed character (`^L`). See `Import Attributes` for more information.

2.11. Exporting from a Database

To export an existing database to a file suitable for searching by Interchange, create a page that contains a `[tag export ...][/tag]` element. Perhaps a better method is to define the same sort of tags in an `OrderProfile`, and use forms and buttons to access the profile.

2.12. Write Control

Interchange databases can be written in the normal course of events, either using the `[import ...]` tag or with a tag like `[data table=table column=field key=code value=new-value]`. To control writing of a global database, or to a certain catalog within a series of subcatalogs, or make one read only, see the following:

To enable write control:

```
Database  products  WRITE_CONTROL  1
```

Once this is done, to make a database read only, which won't allow writing even if `[tag flag`

`write]products[/tag]` is specified:

```
Database    products    READ_ONLY    1
```

To have control with `[tag flag write]products[/tag]`:

```
Database    products    WRITE_TAGGED    1
```

To limit write to certain catalogs, set:

```
Database    products    WRITE_CATALOG    simple=0, sample=1
```

The "simple" catalog will not be able to write, while "sample" will if `[tag flag write]products[/tag]` is enabled. If a database is to always be writable, without having to specify `[tag flag write] ... [/tag]`, then define:

```
Database    products    WRITE_ALWAYS    1
```

The default behavior of SQL databases is equivalent to `WRITE_ALWAYS`, while the default for `GDBM_File`, `DB_File`, and `Memory` databases is equivalent to:

```
Database    products    WRITE_CONTROL    1
Database    products    WRITE_TAGGED    1
```

2.13. Global Databases

If a database is to be available to all catalogs on the Interchange server, it may be defined in `minivend.cfg`. Any catalog running under that server will be able to use it. It is writable by any catalog unless `WRITE_CONTROL` is used.

3. SQL Support

Interchange can use any of a number of SQL databases through the powerful Perl DBI/DBD access methods. This allows transparent access to any database engine that is supported by a DBD module. The current list includes mSQL, MySQL, Solid, PostgreSQL, Oracle, Sybase, Informix, Ingres, Dbase, DB2, Fulcrum, and others. Any ODBC (with appropriate driver) should also be supported.

No SQL database is included with Interchange, but there are a number widely available on the Internet. Most commonly used with Interchange are PostgreSQL, MySQL, and Oracle. It is beyond the scope of this document to describe SQL or DBI/DBD. Sufficient familiarity is assumed.

In most cases, Interchange cannot perform administrative functions, like creating a database or setting access permissions. This must be done with the tools provided with a SQL distribution. But, if given a blank database and the permission to read and write it, Interchange can import ASCII files and bootstrap from there.

3.1. SQL Support via DBI

The configuration of the DBI database is accomplished by setting attributes in additional Database directives after the initial defining line as described above. For example, the following defines the database **arbitrary** as a DBI database, sets the data source (DSN) to an appropriate value for an mSQL database named minivend on port 1114 of the local machine:

```
Database arbitrary arbitrary.asc SQL
Database arbitrary DSN          dbi:mSQL:minivend:localhost:1114
```

As a shorthand method, include the DSN as the type:

```
Database arbitrary arbitrary.asc dbi:mSQL:minivend:localhost:1114
```

Supported configuration attributes include (but are not limited to):

DSN

A specification of the DBI driver and its data source. To use the DBD::mSQL driver for DBI, use:

```
dbi:mSQL:minivend:othermachine.my.com:1112
```

where mSQL selects the driver (case IS important), minivend selects the database, othermachine.my.com selects the host, and 1112 is the port. On many systems, dbi:mSQL:minivend will work fine. Of course, the minivend database must already exist. This is the same as the DBI_DSN environment variable, if the DSN parameter is not set. Then, the value of DBI_DSN will be used to try and find the proper database to connect to.

USER

The user name used to log into the database. It is the same as the environment variable **DBI_USER**. If a user name is not needed, just don't set the USER directive.

PASS

The password used to log into the database. It is the same as the environment variable **DBI_PASS**. If a password is not needed, just don't set the PASS directive.

COLUMN_DEF

A comma-separated set of lines in the form NAME=TYPE(N), where NAME is the name of the field/column, TYPE is the SQL data type reference, and N is the length (if needed). Most Interchange fields should be the fixed-length character type, something like char(128). In fact, this is the default if a type is not chosen for a column. There can be as many lines as needed. This is not a DBI parameter, it is specific to Interchange.

NAME

A space-separated field of column names for a table. Normally not used. Interchange should resolve the column names properly upon query. Set this if a catalog errors out with "dbi: can't find field names" or the like. The first field should always be **code**. This is not a DBI parameter, it is specific to Interchange. All columns must be listed, in order of their position in the table.

NUMERIC

Tells Interchange not to quote values for this field. It allows numeric data types for SQL databases. It is placed as a comma-separated field of column names for a table, in no particular order. This should be defined if a numeric value is used because many DBD drivers do not yet support type queries.

UPPERCASE

Tells Interchange to force field names to UPPER case for row accesses using the [item-data ...], [loop-data ...], [item-field ...], etc. Typically used for Oracle and some other SQL implementations.

DELIMITER

A Interchange delimiter type, either TAB,CSV,PIPE,%%,LINE or the corresponding numeric type. The default for SQL databases is TAB. Use DELIMITER if another type will be used to import. This is not a DBI parameter. It is specific to Interchange.

KEY

The keying default of code in the first column of the database can be changed with the KEY directive. Don't use this unless prepared to alter all searches, imports, and exports accordingly. It is best to just accept the default and make the first column the key for any Interchange database.

ChopBlanks, LongReadLen, LongTruncOK, RaiseError, etc.

Sets the corresponding DBI attribute. Of particular interest is ChopBlanks, which should be set on drivers which by default return space-padded fixed-length character fields (Solid is an example).

The supported list as of this release of Interchange is:

```
ChopBlanks
CompatMode
LongReadLen
```

```

LongTruncOk
PrintError
RaiseError
Warn

```

Issue the shell command `perldoc DBI` for more information.

Here is an example of a completely set up DBI database on MySQL, using a comma-separated value input, setting the DBI attribute `LongReadLen` to retrieve an entire field, and changing some field definitions from the default `char(128)`:

```

Database products products.csv dbi:mysql:minivend
Database products USER minivend
Database products PASS nevairbe
Database products DELIMITER CSV

# Set a DBI attribute
Database products LongReadLen 128

# change some fields from the default field type of char(128)
# Only applies if Interchange is importing from ASCII file
# If you set a field to a numeric type, you must set the
# NUMERIC attribute
Database products COLUMN_DEF "code=char(20) NOT NUL primary key"
Database products COLUMN_DEF price=float, discount=float
Database products COLUMN_DEF author=char(40), title=char(64)
Database products COLUMN_DEF nontaxable=char(3)
Database products NUMERIC price
Database products NUMERIC discount

```

MySQL, DBI, and `DBD::mysql` must be completely installed and tested, and have created the database `minivend`, for this to work. Permissions are difficult on MySQL. If having trouble, try starting the MySQL daemon with `safe_mysqld --skip-grant-tables` & for testing purposes.

To change to ODBC, the only changes required might be:

```

Database products DSN dbi:ODBC:TCP/IP localhost 1313
Database products ChopBlanks 1

```

The DSN setting is specific to a ODBC setup. The `ChopBlanks` setting takes care of the space-padding in Solid and some other databases. It is not specific to ODBC. Once again, DBI, `DBD::ODBC`, and the appropriate ODBC driver must be installed and tested.

3.2. SQL Access Methods

An Interchange SQL database can be accessed with the same tags as any of the other databases can. Arbitrary SQL queries can be passed with the `[query sql="SQL STATEMENT"]` MML tag.

3.3. Importing from an ASCII File

When importing a file for SQL, Interchange by default uses the first column of the ASCII file as the primary key, with a `char(16)` type, and assigns all other columns a `char(128)` definition. These definitions can be changed by placing the proper definitions in `COLUMN_DEF` Database directive attribute:

Interchange Databases

```
Database products COLUMN_DEF price=char(20), nontaxable=char(3)
```

This can be set as many times as desired, if it will not fit on the line.

```
Database products COLUMN_DEF price=char(20), nontaxable=char(3)
Database products COLUMN_DEF description=char(254)
```

To create an index automatically, append the information when the value is in quotes:

```
Database products COLUMN_DEF "code=char(14) primary key"
```

The field delimiter to use is TAB by default, but can be changed with the Database DELIMITER directive:

```
Database products products.csv dbi:mysql:minivend:localhost:1114
Database products DELIMITER CSV
```

To create other secondary keys to speed sorts and searches, do so in the COLUMN_DEF:

```
Database products COLUMN_DEF "author=char(64) secondary key"
```

Or use external database tools. NOTE: Not all SQL databases use the same index commands.

To use an existing SQL database instead of importing, set the NoImport directive in catalog.cfg to include any database identifiers not to be imported:

```
NoImport products inventory
```

WARNING: If Interchange has write permission on the products database, be careful to set the NoImport directive or create the proper .sql file. If that is not done, and the database source file is changed, the SQL database could be overwritten. In any case, always back up the database before enabling it for use by Interchange.

4. The Search Engine

Interchange implements a search engine which will search the product database (or any other file) for items based on customer input. It uses either forms or link-based searches that are called with the special page name `scan`. The search engine uses many special Interchange tags and variables.

If the search is implemented in a link or a form, it will always display formatted results on the results page, an Interchange page that uses some combination of the `[search-region]`, `[search-list]`, `[more-list]`, `[more]`, and other Interchange tags to format and display the results. The search results are usually a series of product codes/SKUs or other database keys, which are then iterated over similar to the `[item-list]`.

Note: Examples of search forms and result pages are included in the demos.

Two search engine interfaces are provided, and five types of searching are available. The default is a text-based search of the first products database source file (i.e., `products.txt`). A binary search of a dictionary-ordered file can be specified. An optional Glimpse search is enabled by placing the command specification for Glimpse in the `catalog.cfg` directive `Glimpse`. There is a range-based search, used in combination with one of the above. And finally, there is a fully-coordinated search with grouping.

The default, a text based search, sequentially scans the lines in the target file. By default it returns the first field (delineated by the delimiter for that database, for every line matching the search specification. This corresponds to the product code, which is then used to key specific accesses to the database.

The text-based search is capable of sophisticated field-specific searches with fully-independent case-sensitivity, substring, and negated matching.

4.1. The Search Form

A number of variables can be set on search forms to determine which search will be used, what fields in the database it will search, and what search behavior will be.

Here is a simple search form:

```
<FORM ACTION="[area search]" METHOD=POST>
<INPUT TYPE="text" SIZE="30" NAME="mv_searchspec">
<INPUT TYPE="submit" VALUE="Search">
</FORM>
```

When the "Search" submit button is pressed (or `<ENTER>` is pressed), Interchange will search the `products.txt` file for the string entered into the text field `mv_searchspec`, and return the product code pertaining to that line.

The same search for a fixed string, say "shirt," could be performed with the use of a hot link, using the special `scan` URL:

```
[page search="se=shirt"]See our shirt collection![/page]
```

Interchange Databases

The default is to search every field on the line. To match on the string "shirt" in the product database field "description," modify the search:

```
<INPUT TYPE="hidden" NAME="mv_search_field" VALUE="description">
```

In the hot-linked URL search:

```
[page search="
    se=shirt
    sf=category
"]See our shirt collection![/page]
```

To let the user decide on the search parameters, use checkboxes or radiobox fields to set the fields:

```
Search by author
<INPUT TYPE="checkbox" NAME="mv_search_field" VALUE="author">
Search by title
<INPUT TYPE="checkbox" NAME="mv_search_field" VALUE="title">
```

Fields can be stacked. If more than one is checked, all checked fields will be searched.

4.2. Glimpse

To use the Glimpse search, the Glimpse index must be built based on files in the ProductDir, or wherever the files to be searched will be located. If Interchange was installed in the default /usr/local/lib/minivend, the command line to build the index for the products file would be:

```
chdir products
glimpseindex -b -H . products.txt
```

There are several ways to improve search speed for large catalogs. One method that works well for large products.txt files is to split the products.txt file into small index files (in the example, 100 lines) with the split(1) UNIX/POSIX command. Then, index it with Glimpse:

```
split -100 products.txt index.txt.
glimpseindex -H /usr/local/lib/minivend/products index.txt.*
```

This will dramatically increase search speeds for large catalogs, at least if the search term is relatively unique. If it is a common string, in a category search, for example, it is better to use the text-based search.

To search for numbers, add the -n option to the Glimpse command line.

Note: A large catalog is one of more than several thousand items; smaller ones have acceptable speed in any of the search modes.

If the Glimpse executable is not found at Interchange startup, the Glimpse search will be disabled and the regular text-based search used instead.

There are several things to watch for while using Glimpse, and a liberal dose of the Glimpse documentation is suggested. In particular, the spelling error capability will not work in combination with the field-specific

search. Glimpse selects the line, but Interchange's text-based search routines disqualify it when checking to see if the search string is within one of the specified fields.

To use field-specific searching on Glimpse, tell it what the field names are. If the search is on the products database (file), nothing is needed for the default is to use the field names from the products database. If it is some other field layout, specify the file to get the field names from with `mv_field_file` (ff).

4.3. Fast Binary Search

Fast binary searching is useful for scanning large databases for strings that match the beginning of a line. They use the standard Perl module `Search::Dict`, and are enabled through use of the `mv_dict_look`, `mv_dict_end`, `mv_dict_limit`, `mv_dict_fold`, and `mv_dict_order` variables.

The field to search is the first field in the file, the product code should be in the second field, delimited by TAB. Set the `mv_return_fields=1` to return the product code in the search.

The search must be done on a dictionary-ordered pre-built index, which can be produced with the database INDEX modifier. See Dictionary indexing with INDEX.

If using the `mv_dict_look` parameter by itself, and the proper index file is present, Interchange will set the options:

```
mv_return_fields=1
mv_dict_limit=-1
```

This will make the search behave much like the simple search described above, except it will be much faster on large files and will match only from the beginning of the field. Here is an example. A `title` index has been built by including in `catalog.cfg`:

```
Database    products    INDEX    title
```

Note: The ASCII source file must be "touched" to rebuild the index and the database.

Now, specify in a form:

```
<FORM ACTION="[process href=search]" METHOD=POST>
<INPUT TYPE=hidden NAME=mv_dict_limit VALUE=title>
<INPUT NAME=mv_dict_look>
</FORM>
```

or in a URL:

```
[page search="dl=Van Gogh/di=title"]
```

This search is case-sensitive. To do the same thing case-insensitively:

```
Database    products    INDEX    title:f

<FORM ACTION="[process href=search]" METHOD=POST>
<INPUT TYPE=hidden NAME=mv_dict_limit VALUE=title>
```

```
<INPUT TYPE=hidden NAME=mv_dict_fold VALUE=1>
<INPUT NAME=mv_dict_look>
</FORM>
```

```
[page search="dl=Van Gogh/di=title/df=1"]
```

4.4. Coordinated and Joined Searching

Interchange will do a complete range of tests on individual columns in the database. To use this function, set `mv_coordinate` to Yes (`co=yes` in the one-click syntax). In order to use coordinated searching, the number of search fields must equal the number of search strings.

To make sure that is the case, use the `mv_search_map` variable. It allows variables to be mapped to others in the search specification. For example:

```
<INPUT TYPE=hidden NAME=mv_search_map VALUE="
  mv_searchspec=search1
  mv_searchspec=search2
  mv_searchspec=search3
">
<INPUT TYPE=hidden NAME=mv_search_field VALUE=title>
<INPUT TYPE=hidden NAME=mv_search_field VALUE=artist>
<INPUT TYPE=hidden NAME=mv_search_field VALUE=category>
Artist: <INPUT NAME=search1 VALUE="">
Title:  <INPUT NAME=search2 VALUE="">
Genre:  <INPUT NAME=search3 VALUE="">
```

Even if the user leaves one blank, the search will work.

Leading/trailing whitespace is stripped from all lines in the `mv_search_map` variable, so it can be positioned as shown for convenience.

Coordinated searches may be joined with the output of another table if set one of the `mv_search_field` values is set to a `table:column` pair. Note that this will slow down large searches considerably unless there is another search specification, as the database must be accessed for every search line. If there is a search field that qualifies for a regular expression search function, or conducting a binary search with `mv_dict_look`, or are not doing an OR search, the penalty should not be too great as only matching lines will cause an access to the database.

Individual field operations can then be specified with the `mv_column_op` (or `op`) parameter. The operations include:

operation	string	numeric	equivalent
equal to	eq	==	=
not equal	ne	!=	<>
greater than	gt	>	
less than	lt	<	
less than/equal to	le	<=	
greater than/equal to	ge	>=	
regular expression	rm		=~ , LIKE
regular expression NOT	rn		!~
exact match	em		

An example:

Interchange Databases

```
[page scan
  co=yes
  sf=title
  se=Sunflowers
  op=em
  sf=artist
  se=Van Gogh
  op=rm          ] Sunflowers, Van Gogh [/page]

[page search="
  co=yes

  sf=title
  se=Sunflowers
  nu=0
  op=!~

  sf=artist
  se=Van Gogh
  op=rm
  nu=0

  sf=inventory:qty
  se=1
  op>=
  nu=1
"] Any in stock except Sunflowers, Van Gogh [/page]
```

Note that in the second example, `nu=0` must be specified even though that is the default. This is to set the proper correspondence. To avoid having to do this, use Interchange's option array feature:

```
[page search.0="
  sf=title
  se=Sunflowers
  op=!~
"
search.1="
  sf=artist
  se=Van Gogh
"
search.2="
  sf=inventory:qty
  se=1
  op>=
  nu=1
"
] Any in stock except Sunflowers, Van Gogh [/page]
```

The `co=yes` is assumed when specifying a multiple search.

The second search will check the stock status of the painting provided there is an inventory table as in some of the Interchange demo catalogs. If the `qty` field is greater than or equal to 1, the product will be picked. If out of stock, it will not be found.

It always helps to have an `rm` type included in the search. This is used to pre-screen records so that database accesses only need be made for already-matching entries. If accesses must be made for every record, large searches can get quite slow.

4.5. Specifying a Text–Based Search with SQL–Like Syntax

If Jochen Wiedmann's `SQL::Statement` module is installed, a SQL syntax can be specified for the text–based search. (This is not the same as the SQL search, treated below separately. It would work on an SQL table, but only on the ASCII text source file, not on the actual database.)

This syntax allows this form setup:

```
Artist: <INPUT NAME="artist">
Title:  <INPUT NAME="title">
<INPUT TYPE=hidden NAME="mv_sql_query"
      VALUE="
        SELECT code FROM products
        WHERE artist LIKE artist
        AND    title LIKE title">
```

If the right hand side of an expression looks like a column, i.e., is not quoted, the appropriate form variable is substituted. (If used in a one–click, the corresponding scratch variable is used instead.) The assumption is reversed for the left–hand side. If it is a quoted string, the column name is read from the passed values. Otherwise, the column name is literal.

```
Search for: <INPUT NAME="searchstring"><BR>
Search in  <INPUT TYPE="radio" NAME="column" VALUE="title"> title
           <INPUT TYPE="radio" NAME="column" VALUE="artist"> artist
           <INPUT TYPE=hidden NAME="mv_sql_query"
           VALUE="SELECT code FROM products WHERE 'column' LIKE searchstring">
```

Once again, this does not conduct a search on an SQL database, but formats a corresponding text–based search. Parentheses will have no effect, and an OR condition will cause all conditions to be OR. The searches above would be similar to:

```
[page search="
    co=yes
    sf=artist
    op=rm
    se=[value artist]
    sf=title
    op=rm
    se=[value title]
" ]
  Search for [value artist], [value title]
[/page]

[page search="
    co=yes
    sf=[value column]
    op=rm
    se=[value searchstring]
" ]
  Search for [value searchstring]
    in [value column]
[/page]
```

4.6. Range Searching

Range searching allows qualification of search returns with a field that must be within a certain numeric or alphanumeric range. To use it, set the `mv_range_look` variable to the products database field, or a column/field number for another file. Then, set the corresponding `mv_range_min` and `mv_range_max` variables with a selectable field.

```
<INPUT TYPE="hidden" NAME="mv_range_look" VALUE="price">
  Search on Price
Min <SELECT NAME="mv_range_min">
  <OPTION value=0 SELECTED> Free
  <OPTION value=1000000> $1,000,000
  <OPTION value=10000000> $10,000,000
  <OPTION value=20000000> $20,000,000
  <OPTION value=40000000> $40,000,000
</SELECT><BR>
Max <SELECT NAME="mv_range_max">
  <OPTION value=0 SELECTED> no object
  <OPTION value=1000000> $1,000,000
  <OPTION value=10000000> $10,000,000
  <OPTION value=20000000> $20,000,000
  <OPTION value=40000000> $40,000,000
</SELECT>
```

The value of 0 for `mv_range_max` is equivalent to infinity if doing a numeric search. This makes it impossible to search for a ceiling of 0 with a negative `mv_range_min`.

The fields are stackable, so more than one range to check can be set. The order is significant, in the sense that the array of field names and minimum/maximum values must be kept in order to achieve correspondence.

The optional `mv_range_alpha` specification allows alphanumeric range matching for the corresponding field. If it is set, and the fields are stacked, they must all be set. The `mv_case` field does apply if it is set. Otherwise, the comparison is without regard to case.

If ONLY a range search is required, all lines with `mv_return_all=yes` must be selected in order to make the search operate. Range-only searches will be quite slow for large databases since every line must be scanned. It should be quite usable for catalogs of less than 10,000 items in size on a fast machine. Using it in combination with another search technique (in the same query) will yield faster search returns.

4.7. One-Click Searches

Interchange allows a search to be passed in a URL, as shown above. Just specify the search with the special page parameter `search` or special page `scan`. Here is an example:

```
[page search="
  se=Impressionists
  sf=category
"]
  Impressionist Paintings
[/page]
```

This is the same:

```
[page scan se=Impressionists/sf=category]
```

Interchange Databases

```
    Impressionist Paintings  
[/page]
```

Here is the same thing from a home page (assuming /cgi-bin/vlink is the CGI path for Interchange's vlink):

```
<A HREF="/cgi-bin/vlink/scan/se=Impressionists/sf=category">  
    Impressionist Paintings  
</A>
```

The two-letter abbreviations are mapped with these letters:

```
ac  mv_all_chars  
bd  mv_base_directory  
bs  mv_begin_string  
co  mv_coordinate  
cs  mv_case  
cv  mv_verbatim_columns  
de  mv_dict_end  
df  mv_dict_fold  
di  mv_dict_limit  
dl  mv_dict_look  
DL  mv_raw_dict_look  
do  mv_dict_order  
dr  mv_record_delim  
em  mv_exact_match  
er  mv_spelling_errors  
ff  mv_field_file  
fi  mv_search_file  
fm  mv_first_match  
fn  mv_field_names  
hs  mv_head_skip  
ix  mv_index_delim  
lb  mv_search_label  
lo  mv_list_only  
lr  mv_search_line_return  
md  mv_more_decade  
ml  mv_matchlimit  
mm  mv_max_matches  
MM  mv_more_matches  
mp  mv_profile  
ms  mv_min_string  
ne  mv_negate  
ng  mv_negate  
np  mv_nextpage  
nu  mv_numeric  
op  mv_column_op  
os  mv_orsearch  
ra  mv_return_all  
rd  mv_return_delim  
rf  mv_return_fields  
rg  mv_range_alpha  
rl  mv_range_look  
rm  mv_range_min  
rn  mv_return_file_name  
rr  mv_return_reference  
rs  mv_return_spec  
rx  mv_range_max  
SE  mv_raw_searchspec  
se  mv_searchspec  
sf  mv_search_field  
sg  mv_search_group
```



```
si mv_search_immediate
sp mv_search_page
sq mv_sql_query
sr mv_search_relate
st mv_searchtype
su mv_substring_match
tc mv_sort_command
td mv_table_cell
tf mv_sort_field
th mv_table_header
to mv_sort_option
tr mv_table_row
un mv_unique
va mv_value
```

These can be treated just the same as form variables on the page, except that they can't contain a new line. If using the multi-line method of specification, the characters will automatically be escaped for a URL.

IMPORTANT NOTE: An incompatibility in earlier Interchange catalogs is specifying [page scan/se=searchstring]. This is interpreted by the parser as [page scan/se="searchstring"] and will cause a bad URL. Change this to [page scan se=searchstring], or perhaps better yet:

```
[page search="
                se=searchstring
            "]
```

A one-click search may be specified in three different ways.

Original

To do an OR search on the fields category and artist for the strings "Surreal" and "Gogh," while matching substrings, do:

```
[page scan se=Surreal/se=Gogh/os=yes/su=yes/sf=artist/sf=category]
    Van Gogh -- compare to surrealists
[/page]
```

In this method of specification, to replace a / (slash) in a file name (for the sp, bd, or fi parameter), the shorthand of :: must be used, i.e., sp=results::standard. (This may not work for some browsers, so put the page in the main pages directory or define the page in a search profile.)

Multi-Line

Specify parameters one to a line, as well.

```
[page scan
    se="Van Gogh"
    sp=lists/surreal
    os=yes
    su=yes
    sf=artist
    sf=category
] Van Gogh -- compare to surrealists [/page]
```

Any "unsafe" characters will be escaped. To search for trailing spaces (unlikely), quote.

Ampersand

Substitute & for / in the specification and be able to use / and quotes and spaces in the specification.

```
[page href=scan se="Van Gogh"&sp=lists/surreal&os=yes&su=yes&sf=artist&sf=category]
  Van Gogh -- compare to surrealists
[/page]
```

Any "unsafe" characters will be escaped.

4.8. Setting Display Options with mv_value

A value can be specified that will be set in the link with the mv_value parameter. It takes an argument of var=value, just as setting a normal variable in an Interchange profile. Actually mv_value is a misnomer, it will almost never be used in a form where variable values can be set. Always specify it in a one-click search with va=var=value. Example:

```
[page href=scan
  arg="se=Renaissance
      se=Impressionists
      va=category_name=Renaissance and Impressionist Paintings
      os=yes"]Renaissance and Impressionist Paintings[/page]
```

Display the appropriate category on the search results page with [value category_name].

4.9. In-Page Searches

To specify a search inside a page with the [search-region parameters*] tag. The parameters are the same as the one-click search, and the output is always a newline-separated list of the return objects, by default, a series of item codes.

The [loop . . .] tag directly accepts a search parameter. To search for all products in the categories "Americana" and "Contemporary," do:

```
[loop search="
  se=Americana
  se=Contemporary
  os=yes
  sf=category9
"]
Artist: [loop-field artist]<BR>
Title: [loop-field title]<P>
[/loop]
```

The advantage of the in-page search is that searches can be embedded within searches, and there can be straight unchanging links from static HTML pages.

To place an in-page search with the full range of display in a normal results page, use the [search-region] tag the same as above, except that [search-list], [more-list], and [more] tags can be placed within it. Use them to display and format the results, including paging. For example:

```
[search-region more=1
```

```
search="
    se=Americana
    sf=category
    ml=2
" ]
[more-list][more][/more-list]
[search-list]
<A MV="page [item-code]" HREF="flypage.html">
    [item-field title]<A>, by [item-field artist]
[/search-list]
[no-match]
    Sorry, no matches for [value mv_searchspec].
[/no-match]
[/search-region]
```

To use the same page for search paging, make sure to set the `sp=page` parameter.

4.10. Search Profiles

An unlimited number of search profiles can be predefined that reside in a file or files. To use this, make up a series of lines like:

```
mv_search_field=artist
mv_search_field=category
mv_orsearch=yes
```

These correspond to the Interchange search variables that can be set on a form. Set it right on the page that contains the search.

```
[set artist_profile]
mv_search_field=artist
mv_search_field=category
mv_orsearch=yes
[/set]
```

This is the same:

```
[set artist_profile]
sf=artist
sf=category
os=yes
[/set]
```

Then, in the search form, set a variable with the name of the profile:

```
<INPUT TYPE=hidden NAME=mv_profile VALUE=artist_profile>
```

In a one-click search, use the `mp` modifier:

```
[page scan se=Leonardo/mp=artist_profile]A left-handed artist[/page]
```

They can also be placed in a file. Define the file name in the `SearchProfile` directive. The catalog must be reconfigured for Interchange to read it. The profile is named by placing a name following a `__NAME__` pragma:

```
__NAME__ title_search
```

The `__NAME__` must begin the line, and be followed by whitespace and the name.

The special variable `mv_last` stops interpretation of search variables. The following variables are always interpreted:

```
mv_dict_look
mv_searchspec
mv_range_look
mv_range_min
mv_range_max
```

Other than that, if `mv_last` is set in a search profile, and there are other variables on the search form, they will not be interpreted.

To place multiple search profiles in the same file, separate them with `__END__`, which must be on a line by itself.

4.11. Search Reference

The supplied `simple/srchform.html` and `simple/results.html` pages show example search forms. Modify them to present the search in any way desired. Be careful to use the proper variable names for passing to Interchange. It is also necessary to copy the hidden variables as-is. They are required to interpret the request as a search.

Note: The following definitions frequently refer to field name and column and column number. All are the references to the columns of a searched text file as separated by delimiter characters.

The field names can be specified in several ways.

ProductFiles

If the file to be searched is left empty in the search form or definition (it is set with `mv_search_file (fi)`), the text files associated with the products databases will be searched, and field names are already available as named in the first line of the file(s). This is defined to be `products.txt` in the Interchange demonstrations.

Be Careful if using SQL! If the database is change and not exported with `[tag export products][/tag]`, searches will not be successful.

Other database files

If the file or files to be searched are ASCII delimited files, and have field names specified on the first line of the file, Interchange will read the first line (of the first file) and determine the field names.

Other files

If the file or files to be searched are ASCII delimited files, but don't have field names specified on the first line of the file, set the variable `mv_field_names` to a comma-separated list of field names as they will be referenced.

Fields can also always be specified by an integer column number, with 0 as the first column.

mv_all_chars

Scan abbreviation: `ac=[1|0]`. Set this if searching is anticipated for lots of punctuation characters that might be special characters for Perl. The characters `()[]\$\^` are included.

mv_base_directory

Scan abbreviation: `bd=/directory/name`. In the text search, set to the directory from which to base file searches. File names without leading `/` characters will be based from there. In the Glimpse search, passed to Glimpse with the `-H` option, and Glimpse will look for its indices there. Default is `ProductDir`.

If an absolute path directory is used, for security enable it in the users session with:

```
[set /directory/name]1[/set]
```

This prevents users from setting an arbitrary value and viewing arbitrary files.

mv_begin_string

If this is set, the string will only match if it is at the beginning of a field. The handling is a bit different for the default AND search compared to the OR search. With OR searches all words are searched for from the beginning of the field, with AND searches all are.

This is a multiple parameter. If `mv_coordinate` is in force, it should be set as many times as necessary to match the field/searchstring combination. If set only once, it applies to all fields. If set more than once but not as many times as the fields, it will default to off.

mv_case

If this item is set to `No`, the search will return items without regard to upper or lower case. This is the default. Set to `Yes` if case should be matched. Implement with a checkbox `<INPUT TYPE=CHECKBOX>` field.

If stacked to match the `mv_search_field` and `mv_searchspec` variables, and `mv_coordinate` is set, it will operate only for the corresponding field.

mv_coordinate

If this item is set to `Yes`, and the number of search fields equals the number of search specs, the search will return only items that match field to spec. (The search specifications are set by stacked `mv_searchspec` and `mv_search_field` variables.)

Case sensitivity, substring matching, and negation all work on a field-by-field basis according to the following:

If only one instance of the option is set, it will affect all fields.

If the number of instances of the option is greater than or equal to the number of search specs, all will be used independently. Trailing instances will be ignored.

If more than one instance of the options are set, but fewer than the number of search specifications, the default setting will be used for the trailing unset options.

If a search specification is blank, it will be removed and all case-sensitivity/negation/substring options will be adjusted accordingly.

mv_dict_end

If the string at the beginning of a line lexically exceeds this value, matching will stop. Ignored without `mv_dict_look`.

mv_dict_fold

Make dictionary matching case-insensitive. Ignored without `mv_dict_look`.

Note: This is the reverse sense from `mv_case`.

mv_dict_limit

Automatically set the limiting string (`mv_dict_end`) to be one character greater than the `mv_dict_look` variable, at the character position specified. A value of 1, for instance, will set the limiting string to "fprsythe" if the value of `mv_dict_look` is "forsythe". A useful value is -1, which will increment the last character (setting the `mv_dict_end` to "forsythf" in our example). This prevents having to scan the whole file once a unique match is found.

Note: The order of this and the `mv_dict_end` variable is significant. Each will overwrite the other.

If this is set to a non-numeric value, an automatic mode is entered which looks for a dictionary-indexed file that corresponds to the file name plus `.field`, where `field` is whatever `mv_dict_limit` is set to. The actual value of `mv_dict_limit` is set to -1. If the file does not exist, the original file is silently used. Also, the value of `mv_return_fields` is set to 1 to correspond to the location of the key in the auto-indexed file. To illustrate:

```
<INPUT TYPE=hidden NAME=mv_dict_limit VALUE=category>
<INPUT TYPE=hidden NAME=mv_search_file VALUE="products.txt">
```

is equal to:

```
<INPUT TYPE=hidden NAME=mv_dict_limit VALUE="-1">
<INPUT TYPE=hidden NAME=mv_search_file VALUE="products.txt.category">
<INPUT TYPE=hidden NAME=mv_return_fields VALUE="1">
```

The real utility would be in a form construct like

```
Search for
<SELECT NAME=mv_dict_limit>
<OPTION> author
<OPTION> title
</SELECT> beginning with <INPUT NAME=mv_dictlook>
```

which would allow automatic binary search file selection.

Combined with the `INDEX` attribute to the Database directive, this allows fast binary search qualification combined with regular `mv_searchspec` text searches.

mv_dict_look

The string at which to begin matching at in a dictionary-based search. If not set, the `mv_dict_end`, `mv_dict_fold`, and `mv_dict_case` variables will be ignored. May be set in a search profile based on other form variables.

mv_dict_order

Make dictionary matching follow dictionary order, where only word characters and whitespace matter. Ignored without `mv_dict_look`.

mv_doit

This must be set to `search` to make this a search page.

mv_exact_match

Normally Interchange searches match words, as opposed to sentences. This behavior can be overridden with `mv_exact_match`, which when set will place quotes around any value in `mv_searchspec` or `mv_dict_look`.

mv_field_names

Deprecated in favor of `in-list` sorting. Defines the field names for the file being searched. This guarantees that they will be available, and prevents a disk access if using named fields on a search file (that is not the product database ASCII source, where field names are already known). This must be exactly correct, or it will result in anomalous search operation. Usually passed in a hidden field or search profile as a comma-separated list.

Note: Use this on the product database only if planning on both pre-sorting with `mv_sort_field` and then post-sorting with `[sort]field:opt[/sort]`.

mv_first_match

Normally Interchange will return the first page of a search. If this variable is set, it will start the search return at the match specified, even if there is only one page. If set to a value greater than the number of matches, it will act as if no matches were found.

mv_head_skip

Normally Interchange searches all lines of an index/product file but the first. Set this to the number of lines to skip at the beginning of the index. Default is 1 for the text search, which skips the header line in the product file. Default is 0 for a Glimpse search.

mv_index_delim

Sets the delimiter for counting fields in a search index. The default is TAB.

mv_matchlimit

The page size for matches that are returned. If more matches than `mv_matchlimit` are found, the search

paging mechanism will be employed if the proper `[more-list]` is present. Can be implemented as a scrolling list (INPUT TYPE=SELECT) or radiobox (INPUT TYPE=RADIO) field.

mv_max_matches

The maximum number of records that will be returned in a search. Default is 2000. This only applies to Glimpse. Use `mv_matchlimit` to set the search page size.

mv_min_string

Sets the minimum size of a search string for a search operation. Default is 4 for the Glimpse search, and 1 for the text search.

mv_negate

Specifies that records NOT matching the search criteria will be returned. Default is no. It is not operative for the Glimpse search.

If stacked to match the `mv_search_field` and `mv_searchspec` variables, and `mv_coordinate` is set, it will operate only for the corresponding field.

mv_orsearch

If this item is set to Yes, the search will return items matching any of the words in `searchspec`. The default is No.

mv_profile

Selects one of the pre-defined search specifications set by the `SearchProfile` directive. If the special variable within that file, `mv_last`, is defined, it will prevent the scanning of the form input for further search modifications. The values of `mv_searchspec` and `mv_dict_look` are always scanned, so specify this to do the equivalent of setting multiple checkboxes or radioboxes with one click, while still reading the search input text.

mv_range_alpha

Sets the type of match, numeric or alphanumeric, for the range search in its corresponding range field. The search will return true, assuming it is greater than the `mv_range_min` specification, if the field searched is less than or equal to `mv_range_max`, in an alphanumeric sense.

mv_range_look

This sets a field to scan for a range of numbers. It must be accompanied with corresponding `mv_range_min` and `mv_range_max` variables. It can be specified with either a field name or a column number.

mv_range_max

Sets the high bound for the range search in its corresponding range field. The search will return true, assuming it is greater than the `mv_range_min` specification, if the field searched is less than or equal to `mv_range_max`. To set the bound at infinity, or whatever your integer limit is, set `mv_range_min` to 0.

mv_range_min

Sets the low bound for the range search in its corresponding range field. The search will return true, assuming it is less than the mv_range_max specification, if the field searched is less than or equal to mv_range_min.

mv_record_delim

Sets the delimiter for counting records in a search index. The default is newline, which works for the products and most line-based index files.

mv_return_fields

The fields that should be returned by the match, specified either by field name or by column number. Specify 0 as the first field to be returned if searching the products database, since that is the key for accessing database fields.

mv_return_spec

Returns the string specified as the search (i.e., the value of mv_searchspec) as the one and only match. Typically used in a SKU/part number search.

mv_search_field

The field(s) to be searched, specified either by column name or by column number.

If the number of instances matches the number of fields specified in the mv_searchspec variable and mv_coordinate is set to true, each search field (in order specified on the form) will be matched with each search spec (again in that order).

mv_search_file

In the text search, set this variable to the file(s) to be scanned for a match. The default, if not set, is to scan the default ProductFiles (i.e., products.txt). If set multiple times in a form (for a text search), will cause a search all the files. One file name per instance.

In the Glimpse search, follows the Glimpse wildcard-based file name matching scheme. Use with caution and a liberal dose of the Glimpse man page.

mv_search_match_count

Set by the search to indicate the total number of matches found.

mv_search_over_msg

The message that should be displayed if there is an overflow condition (mv_matchlimit is exceeded). Overrides the SearchOverMsg directive. It is cleared by Interchange if there is no overflow. Somewhat deprecated by match paging.

mv_search_page

The Interchange-style name of the page that should display the search results. Overrides the FrameSearchPage directive, and the default value of search.

mv_searchspec

The actual search string that is typed in by the customer. It is a text INPUT TYPE=TEXT field, or can be put in a select (drop-down) list to enable category searches. If multiple instances are found, they will be concatenated just as if multiple words had been placed in a text field.

The user can place quotes around words to specify that they match as a string. To enable this by default, use the `mv_exact_match` variable.

If `mv_dict_look` has a value, and `mv_searchspec` does not, then `mv_searchspec` will be set to the value of `mv_dict_look`.

If the number of instances matches the number of fields specified in the `mv_search_field` variable and `mv_coordinate` is set to true, each search field (in order specified on the form) will be matched with each search spec (again in that order).

mv_searchtype

If set to Glimpse, selects the Glimpse search (if Glimpse is defined).

If set to db, iterates over every row of the database (not the associated text source file).

If set to sql, same as db.

If set to text, selects the text-based search.

When using `st=db`, returned keys may be affected by `TableRestrict`. See `CATALOG.CFG`.

Defaults to text if Glimpse is not defined; defaults to Glimpse if it is defined. This can allow use of both search types if that is desirable. For instance, searching for very common strings is better done by the text-based search. An example might be searching for categories of items instead of individual items.

mv_sort_field

The file field(s) the search is to be sorted on, specified in one of two ways. If the file(s) to be searched have a header line (the first line) that contains delimiter-separated field names, it can be specified by field name. It can also be specified by column number (the code or key is specified with a value of 0, for both types). These can be stacked if coming from a form or placed in a single specification separated by commas.

Note: If specifying a sort for the product database, `mv_field_names` must be specified if doing a fieldname-addressed post-sort.

mv_sort_option

The way that each field should be sorted. The flags are `r`, `n`, and `f`, reverse, numeric, and case-insensitive respectively. These can be stacked if coming from a form or placed in a single specification separated by commas. The stacked options will be applied to the sort fields as they are defined, presuming those are stacked.

mv_spelling_errors

The number of spelling errors that will be tolerated. Ignored unless using Glimpse. For a large catalog, limit this to two.

mv_substring_match

If `mv_substring_match` is set to Yes, matches on substrings as well as whole words. Typically set this

for dictionary-based searches.

If stacked to match the `mv_search_field` and `mv_searchspec` variables and `mv_coordinate` is set, it will operate only for the corresponding field.

mv_unique

If set to a true value, causes the sort to return only unique results. This operates on whatever the search return is, as defined by `mv_return_fields`.

mv_value

This is normally only used in the one-click search (`va=var=value`). It allows setting of a session variable based on the clicked link, which makes for easy definition of headers and other display choices. (If had trouble using `mv_searchspec` for this before, this is what is needed.)

4.12. The Results Page

Once a search has been completed, there needs to be a way of presenting the output. By default, the `SpecialPage` search is used. It is set to `results` in the distribution demo, but any number of search pages can be specified by passing the value in the search form specified in the variable `mv_search_page`.

On the search page, some special Interchange tags are used to format the otherwise standard HTML. Each of the iterative tags is applied to every code returned from the search. This is normally the product code, but could be a key to any of the arbitrary databases. The value placed by the `[item-code]` tag is set to the first field returned from the search.

The basic structure looks like this:

```
[search-region]
[search-list]
    your iterating code, once for each match
[/search-list]
[no-match]
    Text / tags to be output if no matches found (optional but recommended)
[/no-match]
[more-list]
    More / paging area (optional)
[/more-list]
[/search-region]
```

TIP FOR MV3 PORTS: A `[search-list][/search-list]` must always be surrounded by a `[search-region][/search-region]` pair. This is a change from Interchange 3.

[search-list]

Starts the representation of a search list. Interchange tags can be embedded in the search list, yielding a table or formatted list of items with part number, description, price, and hyperlinks to order or go to its catalog page.

The example tags shown have an `item-` prefix, which is the default. Set any prefix desired with the `prefix` parameter to `[search-region]`:

```
[search-region prefix=my]
[search-list]
```

Interchange Databases

```
SKU:    [my-code]
Title:  [my-data products title]
[/search-list]
[/search-region]
```

The standard set of Interchange iterative ITL tags are available. They are interpolated in this order:

```
[item-alternate N] true [else] false [/else] [/item-alternate]
[if-item-param named_field] true [else] false [/else] [/if-item-param]
[item-param named_field]
[if-item-pos N] true [else] false [/else] [/if-item-pos]
[item-pos N]
[if-item-field products_field] true [else] false [/else] [/if-item-field]
[item-field products_column]
[item-increment]
[item-accessories]
[item-code]
[item-description]
[if-item-data table column] true [else] false [/else] [/if-item-data]
[item-data table column]
[item-price N* noformat=1*]
[item-calc] [/item-calc]
[item-change marker]
    [condition]variable text[/condition]
    true
    [else] false [/else]
[/item-change marker]
[item-last] condition [/item-last]
[item-next] condition [/item-next]
```

Note: those that reference the shopping cart do not apply, i.e., [item-quantity], [item-modifier ...] and friends.

[/search-list]

Ends the search list.

[no-match]

Starts the region of the search results page that should be returned if there is no match (and no error) for the search. If this is not on the page, the special page nomatch will be displayed instead.

[/no-match]

Ends the no match region.

[sort database:field:option* database:field:option*]

Sorts the search list return based on database fields. If no options are supplied, sorts according to the return code. See SORTING.

This is slow, and it is far better to pre-sort the return in the search specification.

[item-change marker]

Active only within [search-list][/search-list].

Along with the companion [/item-change marker], surrounds a region which should only be output when a field (or other repeating value) changes its value. This allows indented lists similar to database reports to be easily formatted. The repeating value must be a tag interpolated in the search process, such as [item-field field] or [item-data database field].

Of course, this will only work as expected when the search results are properly sorted.

The marker field is mandatory, and is also arbitrary, meaning that any marker can be selected as long as it matches the marker associated with [/item-change marker]. The value to be tested is contained within a [condition]value[/condition] tag pair. The [item-change marker] tag also processes an [else] [/else] pair for output when the value does not change. The tags may be nested as long as the markers are different.

The following is a simple example for a search list that has a field category and subcategory associated with each item:

```
<TABLE>
<TR><TH>Category</TH><TH>Subcategory</TH><TH>Product</TH></TR>
[search-list]
<TR>
  <TD>
    [item-change cat]

    [condition][item-field category][ /condition]

    [item-field category]
  [else]
    &nbsp;
  [ /else]
  [ /item-change cat]
</TD>
  <TD>
    [item-change subcat]

    [condition][item-field subcategory][ /condition]

    [item-field subcategory]
  [else]
    &nbsp;
  [ /else]
  [ /item-change subcat]
</TD>
  <TD> [item-field name] </TD>
[/search-list]
</TABLE>
```

The above should output a table that only shows the category and subcategory once, while showing the name for every product. (The will prevent blanked table cells if using a border.)

[/item-change marker]

Companion to [item-change marker].

[matches]

Replaced with the range of match numbers displayed by the search page. Looks something like "1–50". Make sure to insert this item between a [more-list] and [/more-list] element pair.

[more-list next_img* prev_img* page_img* border* border_current*]

Starts the section of the search page which is only displayed if there are more matches than specified in `mv_matchlimit`. If there are less matches than the number in `mv_matchlimit`, all text/html between the `[more_list]` and `[/more_list]` elements is stripped.

Use in conjunction with the `[more]` element to place pointers to additional pages of matches.

If the optional arguments `next_img`, `prev_img`, and/or `page_img` are present, they represent image files that will be inserted instead of the standard 'Next,' 'Previous,' and page number. If `prev_img` is none, then no previous link will be output. If `page_img` is none, then no links to pages of matches will be output. These are URLs, are substituted for with *ImageDir* and friends, and will be encased in IMG tags. Lastly, `border` is the border number to put.

In addition, if `page_img` is used, it will be passed an argument of the digit that is to be represented. This would allow an image generator program to be used, generating page numbers on the fly. The `border` and `border_selected` values are integers indicating the border that should be put around images in the `page_img` selection. The `<border_selected>` is used for the current page if set.

\Examples:

`[more-list next.gif prev.gif page_num.cgi 3]` causes anchors of:

```
Previous    <IMG SRC="prev.gif" Border=3>
Page 1     <IMG SRC="/cgi-bin/page_num.cgi?1">
Page 2     <IMG SRC="/cgi-bin/page_num.cgi?2">
Next       <IMG SRC="next.gif" Border=3>
```

`[more-list next.gif prev.gif page_num.cgi]` causes anchors of:

```
Previous    <IMG SRC="prev.gif">
Page 1     <IMG SRC="/cgi-bin/page_num.cgi?1">
Page 2     <IMG SRC="/cgi-bin/page_num.cgi?2">
Next       <IMG SRC="next.gif">
```

`[more-list next.gif prev.gif 0 0]` causes anchors of:

```
Previous    <IMG SRC="prev.gif" Border=0>
Page 1     <IMG SRC="/cgi-bin/page_num.cgi?1">
Page 2     <IMG SRC="/cgi-bin/page_num.cgi?2">
Next       <IMG SRC="next.gif" Border=0>
```

To set custom text for the "Previous" and "Next" usually used, define the `next_img`, `prev_img`, and `page_img` with `[next-anchor][/next-anchor]`, `[prev-anchor][/prev-anchor]` and `[page-anchor][/page-anchor]`. The string `$PAGE$` will be replaced with the page number in the latter. The same example:

```
[more-list 0 0 0]
[next-anchor] Forward [/next-anchor]
[prev-anchor] Back [/prev-anchor]
[page-anchor] Page $PAGE$ [/page-anchor]
[more]
[/more-list]
```

will display Forward Page 1 Page 2 Back for 2 pages.

As shown, pass a 0 for the arguments of each to tell Interchange to look for the assignments.

If have many pages of matches and don't wish to have all displayed at once, set

`[decade-next][/decade-next]` and `[decade-prev][/decade-prev]`. If set them empty, a search with 31 pages will display pages 21–30 like:

Interchange Databases

Previous 1 2 3 4 5 6 7 8 9 10 [more>>] Next

and pages 11–20 like:

Previous [<<more] 11 12 13 14 15 16 17 18 19 20 [more>>] Next

If set to [decade-next](higher)[/decade-next] and [decade-prev](lower)[/decade-prev], the following will be displayed:

Previous (lower) 11 12 13 14 15 16 17 18 19 20 (higher) Next

Of course, image-based anchors can be used as well.

[/more-list]

Companion to [more-list].

[more]

Inserts a series of hyperlinks that will call up the next matches in a series. They look like this:

Previous 1 2 3 4 5 6 Next

The current page will not be a hyperlink. Every time the new link is pressed, the list is re-built to correspond to the current page. If there is no Next or Previous page, that link will not be shown.

See the `fr_resul.html` or `search.html` files for examples. Make sure to insert this item between a [more-list] and [/more-list] element pair.

[process-search]

Calls the search with the proper URL, including Interchange session tags. Used as the ACTION value for the search form.

[process-target frame]

Calls the search with the proper URL, including Interchange session tags. Used as the ACTION value for the search form if the results are to be targeted to a different window than the one set by SearchFrame (which is "_self" by default).

5. Sorting

Interchange has standard sorting options for sorting the search lists, loop lists, and item lists based on the contents of database fields. In addition, it adds list slices for limiting the displayed entries based on a start value and chunk size (or start and end value, from which a chunk size is determined). All accept a standard format sort tag which must be directly after the list call:

```
[loop 4 3 2 1]
[sort -2 +2]
    [loop-code]
[/loop]

[search-list]
[sort products:category:f]
    [item-price] [item-description]<BR>
[/search-list]

[item-list]
[sort products:price:rn]
    [item-price] [item-code]<BR>
[/item-list]

[loop search="ra=yes"]
[sort products:category products:title]
[loop-field category] [loop-field title] <BR>
[/loop]
```

All sort situations, [search list], [loop list], [tag each table], and [item-list], take options of the form:

```
[sort database:field:option* -n +n =n-n ... ]
```

database

The Interchange database identifier. This must be supplied and should normally be 'products' if using the default name for the database.

field

The field (column) of the database to be sorted on.

option

None, any, or combinations of the options:

```
f    case-insensitive sort (folded) (mutually exclusive of n)
n    numeric order (mutually exclusive of f)
r    reverse sort
```

-n

The starting point of the list to be displayed, beginning at 1 for the first entry.

+n

The number of entries to display in this list segment.

=n-n

The starting and ending point of the list display. This is an alternative to `-n` and `+n`. They should be specified in only one form. If both are specified, the last one will take effect.

...

Don't really put . . . in. This means that many sort levels are specified. Lots of sort levels with large databases will be quite slow.

Multiple levels of sort are supported, and database boundaries on different sort levels can be crossed. Cross-database sorts on the same level are not supported. If using multiple product databases, they must be sorted with embedded Perl. This is actually a feature in some cases, all items in a used database can be displayed before or after new ones in `products`.

Examples, all based on the `simple` demo:

Loop list

```
[loop 00-0011 19-202 34-101 99-102]
[sort products:title]
    [loop-code] [loop-field title]<BR>
[/loop]
```

Will display:

```
34-101 Family Portrait
00-0011 Mona Lisa
19-202 Radioactive Cats
99-102 The Art Store T-Shirt
```

\Alternatively:

```
[loop 00-0011 19-202 34-101 99-102]
[sort products:title -3 +2]
    [loop-code] [loop-field title]<BR>
[/loop]
```

\Displays:

```
19-202 Radioactive Cats
99-102 The Art Store T-Shirt
```

The tag `[sort products:title =3-4]` is equivalent to the above.

Search list

A search of all products (i.e., <http://yoursystem.com/cgi-bin/simple/scan/ra=yes>):

```
[search-list]
[sort products:artist products:title:rf]
    [item-field artist] [item-field title]<BR>
```

```
[/search-list]
```

will display:

```
Gilded Frame
Grant Wood American Gothic
Jean Langan Family Portrait
Leonardo Da Vinci Mona Lisa
Salvador Dali Persistence of Memory
Sandy Skoglund Radioactive Cats
The Art Store The Art Store T-Shirt
Vincent Van Gogh The Starry Night
Vincent Van Gogh Sunflowers
```

Note the reversed order of the title for Van Gogh and the presence of the accessory item Gilded Frame at the front of the list. It has no artist field and, as such, sorts first).

Adding a slice option:

```
[search-list]
[sort products:artist products:title:rf =6-10]
  [item-field artist] [item-field title]<BR>
[/search-list]
```

will display:

```
Sandy Skoglund Radioactive Cats
The Art Store The Art Store T-Shirt
Vincent Van Gogh The Starry Night
Vincent Van Gogh Sunflowers
```

If the end value/chunk size exceeds the size of the list, only the elements that exist will be displayed, starting from the start value.

Shopping cart

```
[item-list]
[sort products:price:rn]
  [item-price] [item-code]<BR>
[/item-list]
```

will display the items in the shopping cart sorted on their price, with the most expensive shown first. NOTE: This is based on the database field and doesn't take quantity price breaks or discounts into effect. Modifier values or quantities cannot be sorted.

Complete database contents

```
[tag each products]
[sort products:category products:title]
[loop-field category] [loop-field title] <BR>
[/tag]
```

A two level sort that will sort products based first on their category, then on their title within the category.

Note that large lists may take some time to sort. If a product database contains many thousands of items, using the `[tag each products]` sort is not recommended unless planning on caching or statically building pages.

6. Shipping

Interchange has a powerful custom shipping facility that performs UPS and other shipper lookups, as well as a flexible rule-based facility for figuring cost by other methods.

6.1. Shipping Cost Database

The shipping cost database (located in ProductDir/shipping.asc) is a tab-separated ASCII file with six fields: code, text description, criteria (quantity or weight, for example), minimum number, maximum number, and cost. None of the fields are case-sensitive.

To define the shipping database in a catalog configuration file, set the Variable MV_SHIPPING to what would be its contents.

To set the file to be something other than shipping.asc in the products directory, set the Special directive:

```
Special shipping.asc /home/user/somewhere/shipping_defs
```

There are two styles of setting which can be mixed in the same file. The first is line-based and expects six or more TAB-separated fields. They would look like:

```
default No shipping weight 0 99999999 0
```

```
upsg UPS Ground weight 0 0 e Nothing to ship! upsg UPS Ground weight 0 150 u Ground [default zip 98366] 3.00 upsg UPS Ground weight 150 999999 e @@TOTAL@@ lbs too heavy for UPS
```

The second is a freeform method with a mode: Description text introducing the mode line. The special encoding is called out by indented parameters. The below is identical to the above:

```
upsg: UPS Ground
  criteria    weight
  min         0
  max         0
  cost        e Nothing to ship!

  min         0
  max         150
  cost        u
  table       2ndDayAir
  geo         zip
  default_geo 98366
  adder       3

  min         150
  max         999999
  cost        e @@TOTAL@@ lbs too heavy for UPS
```

The second format has several advantages. Multiple lines can be spanned with the <<HERE document format, like so:

```
upsg: UPS Ground
  criteria    <<EOF
```

Interchange Databases

```
[perl]
  return 'weight' if $Values->{country} eq 'US';
  return 'weight' if ! $Values->{country};
  # Return blank, don't want UPS
  return '';
[/perl]
EOF
```

The definable fields are, in order, for the tab-separated format:

MODE

The unique identifier for that shipping method. It may be repeated as many times as needed.

DESCRIPTION

Text to describe the method (can be accessed on a page with the [shipping-description] element).

CRITERIA

Whether shipping is based on weight, quantity, price, etc. Valid Interchange tags can be placed in the field to do a dynamic lookup. If a number is returned, that is used as the accumulated criteria. That is, the total of weight, quantity, or price as applied to all items in the shopping cart. See Criteria Determination below.

MINIMUM

The low bound of quantity/weight/criteria this entry applies to.

MAXIMUM

The high bound of quantity/weight/criteria this entry applies to. The first found entry is used in case of ties.

COST

The method of developing cost. It can be a number which will be used directly as the shipping cost, or a function, determined by a single character at the beginning of the field:

f	Formula (MML tags OK, evaluated as Perl)
x	Multiplied by a number
[uA-Z]	UPS-style lookup
m	Interchange chained cost lookup (all items summed together)
i	Interchange chained cost lookup (items summed individually)

NEXT

The next field supplies an alternative shipping mode to substitute if the cost of the current one is zero.

ZONE

The UPS zone that is being defined.

QUERY

Interchange tags which will return a SQL query to select lines matching this specification. The current mode is replaced with this selection. If there is a query parameter of `?`, it will be replaced with the mode name.

QUAL

The geographic qualification (if any) for this mode.

PERL

Perl code that is read and determines the criterion, not the cost. Use the `cost` option with "f" as the prelim to supply Perl code to determine cost.

TOTAL

Set to the accumulated criterion before passing to Perl.

OPT

Used to maintain UPS and freeform options. Normally these are set by separate lines in the shipping definition.

6.2. Criteria Determination

The criteria field varies according to whether it is the first field in the shipping file exactly matching the mode identifier. In that case, it is called the main criterion. If it is in subsidiary shipping lines matching the mode (with optional appended digits), it is called a qualifying criterion. The difference is that the main criterion returns the basis for the calculation (i.e., weight or quantity), while the qualifying criterion determines whether the individual line may match the conditions.

The return must be one of:

quantity

The literal value quantity as the main criterion will simply count the number of items in the shopping cart and return it as the accumulated criteria. If using a database table field named `quantity`, use the `table::field` notation.

o <field name> or <table>::<field name>

A valid database field (column) name as main criterion will cause the number of items in the shopping cart to be multiplied by the value of the field for each item to obtain the accumulated criteria. If the table is not supplied, defaults to the first `ProductFiles` table.

o n.nn

Where **n.nn** is any number, it will be directly used as the accumulated criteria. This can be effectively returned from a Perl subroutine or Interchange `[calc][item-list] ...`
`[/item-list][/calc]` to create custom shipping routines.

IMPORTANT NOTE: The above only applies to the first field that matches the shipping mode exactly. Following criteria fields contain qualifier matching strings.

6.3. Shipping Calculation Modes

There are eight ways that shipping cost may be calculated. The method used depends on the first character of the `cost` field in the shipping database.

N.NN (digits)

If the first character is a digit, a number is assumed and read directly as the shipping cost.

e

If the first character is an `e`, a cost of zero is returned and an error message is placed in the session value `ship_message` (i.e., `[data session ship_message]` or `$Session->{ship_message}`).

f

If the character `f` is the first, Interchange will first interpret the text for any Interchange tags and then interpret the result as a formula. It is read as Perl code; the entire set of Interchange objects may be referenced with the code.

i

Specifies a chained shipping lookup which will be applied to each item in the shopping cart.

m

Specifies a chained shipping lookup which will be applied to the entire shopping cart.

u

Calls the UPS-style lookup. Can pre-define as many as desired. Though if want to do the hundreds available, it is best done on-the-fly.

x

If an `x` is first, a number is expected and is applied as a fixed multiplier for the accumulated criterion (`@@TOTAL@@`).

A-Z

If the first character is a capital letter, calls one of the 26 secondary UPS-style lookup zones. (Deprecated now that zones can be named directly).

6.4. How Shipping is Calculated

1. The base code is selected by reading the value of `mv_shipmode` in the user session. If it has not been explicitly set, either by means of the `DefaultShipping` directive or by setting the variable on a form (or in an order profile), it will be `default`.
The `mv_shipmode` must be in the character class `[A-Za-z0-9_]`. If there are spaces, commas, or nulls in the value, they will be read as multiple shipping modes.
2. The modes are selected from the `d`
The criterion field is found. If it is quantity, it is the total quantity of items on the order form. If it is any other name, the criterion is calculated by multiplying the return value from the product database field for each item in the shopping cart, multiplied by its quantity. If the lookup fails due to the column or row not existing, a zero cost will be returned and an error is sent to the catalog error log. If a number is returned from an Interchange tag, that number is used directly.
Entries in the shipping database that begin with the same string as the shipping mode are examined. If none is found, a zero cost is returned and an error is sent to the catalog error log.

Note: The same mode name may be used for all lines in the same group, but the first one will contain the main criteria.

1. The value of the accumulated criteria is examined. If it falls within the minimum and maximum, the cost is applied.
2. If the cost is fixed, it is simply added.
3. If the cost field begins with an `x`, the cost is multiplied by the accumulated criterion, i.e., price, weight, etc.
4. If the cost field begins with `f`, the formula following is applied. Use `@@TOTAL@@` as the value of the accumulated criterion.
5. If the cost field begins with `u` or a single letter from `A-Z`, a UPS-style lookup is done.
6. If the cost field begins with `s`, a Perl subroutine call is made.
7. If the cost field begins with `e`, zero cost is returned and an error placed in the session **ship_message** field, available as `[data session ship_message]`.

Here is an example shipping file using all of the methods of determining shipping cost.

Note: The columns are lined up for reading convenience. The actual entries should have ONE tab between fields.

global Option n/a 0 0 g PriceDivide

rpsg RPS quantity 0 0 R RPS products/rps.csv rpsg RPS quantity 0 5 7.00 rpsg RPS quantity 6 10 10.00 rpsg RPS quantity 11 150 x .95

usps US Post price 0 0 0 usps US Post price 0 50 f 7 + (1 * @@TOTAL@@ / 10) usps US Post price 50 100 f 12 + (.90 * @@TOTAL@@ / 10) usps US Post price 100 99999 f @@TOTAL@@ * .05

upsg UPS weight [value 0 e Nothing to ship state]0. upsg UPS AK HI 0 150 u upsg [default zip 980] 12.00 round upsg UPS 0 150 u Ground [default zip 980] 2.00 round upsg UPS 150 9999 e @@TOTAL@@ lb too

heavy for UPS

```
upsca UPS/CA weight 0 0 c C UPS_Canada products/can.csv upsca UPS/CA weight -1 -1 o PriceDivide=0
upsca UPS/CA weight 0 150 C upsca [default zip A7G] 5.00 upsca UPS/CA weight 150 99999 e
@@TOTAL@@ lb too heavy for UPS
```

global

This is a global option setting, called out by the `g` at the beginning. PriceDivide tells the shipping routines to multiply all shipping settings by the PriceDivide factor, except those explicitly set differently with the `o` individual modifier. This allows currency conversion. (Currently the only option is PriceDivide.)

rpsh

If the user selected RPS, (code `rpsh`) and the quantity on the order was 3, the cost of 7.00 from the second `rpsh` line would be applied. If the quantity were 7, the next entry from the third `rpsh` line would be selected for a cost of 10.00. If the quantity were 15, the last `rpsh` would be selected and the quantity of 15 multiplied by 0.95, for a total cost of 14.25.

usps

The next mode, `usps`, is a more complicated formula using price as the criteria. If the total price of all items in the shopping cart (same as `[subtotal]` without quantity price breaks in place) is from 1 to 50, the cost will be 7.00 plus 10 percent of the order. If the total is from 50.01 to 100, the cost will be 12.00 plus 9 percent of the order total. If the cost is 100.01 or greater, 5 percent of the order total will be used as the shipping cost.

upsg

The next, `upsg`, is a special case. It specifies a UPS lookup based on the store's UPS zone and two required values (and two optional arguments):

1. Weight
2. The zip/postal code of the recipient of which only the first three digits are used.
3. A fixed amount to add to the cost found in the UPS tables (use 0 as a placeholder if specifying roundup)
4. If set to 'round,' will round the cost up to the next integer monetary unit.

If the cost returned is zero, the reason will be placed as an error message in the session variable `ship_message` (available as `[data session ship_message]`).

UPS weights are always rounded up if any fraction is present.

The routines use standard UPS lookup tables. First, the UPS Zone file must be present. That is a standard UPS document specific to the retailer's area that must be obtained from UPS. It is entered into and made available to Interchange in TAB-delimited format. (As of March 1997, use the standard .csv file distributed by UPS on their Web site at www.ups.com.) Specify it with the `UpsZoneFile` directive. It is usually named something like `NNN.csv`, where NNN is the first three digits of the originating zip code. If placed in the products directory, the directive would look like:

```
UpsZoneFile products/450.csv
```

Second, obtain the cost tables from UPS (again, get them from `www.ups.com`) and place them into an Interchange database. That database, its identifier specified with the first argument (Ground in the example) of the cost specification, is consulted to determine the UPS cost for that weight and rate schedule. In the example below, use a database specification like:

```
Database Ground Ground.csv CSV
```

A simple shipping cost qualification can be appended to a UPS lookup. If any additional parameters are present after the five usual ones used for UPS lookup, they will be interpreted as a Perl subroutine call. The syntax is the same as if it was encased in the tag `[perl sub] [/perl]`, but the following substitutions are made prior to the call:

```
@@COST@@ is replaced with whatever the UPS lookup returned
@@GEO@@  is replaced with the zip (or other geo code)
@@ADDER@@ is replaced with the defined adder
@@TYPE@@ is replaced with the UPS shipping type
@@TOTAL@@ is replaced with the total weight
```

The example above also illustrates geographic qualification. If the value of the form variable `state` on the checkout form is `AK` or `HI`, the U.S. states Alaska and Hawaii, a \$10.00 additional charge (over and above the normal \$2.00 handling charge) is made. This can also be used to select on country, product type, or any other qualification that can be encoded in the file.

upsca

The next entry is just like the UPS definition except it defines a different lookup zone file (`products/can.csv`) and uses a different database, `upsca`. It also disables the global `PriceDivide` option for itself only, not allowing currency conversion. Otherwise, the process is the same. Up to 27 different lookup zones can be defined in the same fashion. If one of the cost lines (the last field) in the `shipping.asc` file begins with a `c`, it configures another lookup zone which must be lettered from `A` to `Z`. It takes the format:

```
c X name file* length* multiplier*
```

where `X` is the letter from `A–Z`. The name is used internally as an identifier and must be present. The optional file is relative to the catalog root (like `UpsZoneFile` is). If it is not present, the file equal to name in the products directory (`ProductDir`) will be used as the zone file. If the optional digit `length` is present, that determines the number of significant digits in the passed postal/geo code.

When the optional `multiplier` is present, the weight is multiplied by it before doing the table lookup. This allows shipping weights in pounds or kilograms to be adapted to a table using the opposite as the key. Remember, the match on weight must be exact, and Interchange rounds the weight up to the next even unit. To define the exact equivalent of the UPS lookup zone, do the following:

```
c U UPS products/450.csv 3 1
```

The only difference is that the beginning code to call the lookup is upper-case `U` instead of lower-case `u`.

6.5. More On UPS–Style Lookup

The UPS–style lookup uses two files for its purposes, both of which need to be in a format like UPS distributes for US shippers.

Interchange Databases

The zone file is a file that is usually specific to the originating location. For US shippers shipping to US locations, it is named for the first three digits of the originating zip code with a CSV extension. For example, 450.csv.

It has a format similar to:

```
low - high, zone,zone,zone,zone
```

The `low` entry is the low bound of the geographic location; `high` is the high bound. (By geographic location, the zip code is meant.) If the first digits of the zip code, compared alphanumerically, fall between the low and high values, that zone is used as the column name for a lookup in the rate database. The weight is used as the row key.

The first operative row of the zone file (one without leading quotes) is used to determine the zone column name. In the US, it looks something like:

```
Dest. ZIP,Ground,3 Day Select,2nd Day Air,2nd Day Air A.M.,Next Day Air Saver,Next Day Air
```

Interchange strips all non-alpha characters and comes up with:

```
DestZIP,Ground,3DaySelect,2ndDayAir,2ndDayAirAM,NextDayAirSaver,NextDayAir
```

Therefore, the zone column (shipping type) that would be used for UPS ground would be "Ground," and that is what the database should be named. To support the above, use a `shipping.asc` line that reads:

```
upsg UPS Ground weight 0 150 u Ground [default zip 983]
```

and a `catalog.cfg` database callout of:

```
Database Ground Ground.csv CSV
```

These column names can be changed as long as they correspond to the `identifier` of the rate database.

The rate database is a standard Interchange database. For U.S. shippers, UPS distributes their rates in a fairly standard comma-separated value format, with weight being the first (or key) column and the remainder of the columns corresponding to the zone which was obtained from the lookup in the zone file.

To adapt other shipper zone files to Interchange's lookup, they will need to fit the UPS US format. (Most of the UPS international files don't follow the U.S. format). For example, the 1998 Ohio-US to Canada file begins:

```
Canada Standard Zone Charts from Ohio
Locate the zone by cross-referencing the first three
characters of the destination Postal Code in the Postal
Range column.
```

Postal	Range	Zone
A0A	A9Z	54
B0A	B9Z	54
C0A	C9Z	54
E0A	E9Z	54
G0A	G0A	51
G0B	G0L	54
G0M	G0S	51

G0T G0W 54

It will need to be changed to:

```
Destination,canstnd
A0A-A9Z, 54
B0A-B9Z, 54
C0A-C9Z, 54
E0A-E9Z, 54
G0A-G0A, 51
G0B-G0L, 54
G0M-G0S, 51
G0T-G0W, 54
```

Match it with a canstnd CSV database that looks like this:

```
Weight,51,52,53,54,55,56
1,7.00,7.05,7.10,11.40,11.45,11.50
2,7.55,7.65,7.75,11.95,12.05,12.10
3,8.10,8.15,8.40,12.60,12.70,12.85
4,8.65,8.70,9.00,13.20,13.30,13.55
5,9.20,9.25,9.75,13.85,13.85,14.20
6,9.70,9.85,10.35,14.45,14.50,14.90
7,10.25,10.40,11.10,15.15,15.15,15.70
8,10.80,10.95,11.70,15.70,15.75,16.35
9,11.35,11.55,12.30,16.40,16.45,17.20
```

It is called out in catalog.cfg with:

```
Database canstnd canstnd.csv CSV
```

With the above, a 4-pound shipment to postal code E5C 4TL would yield a cost of 13.20.

6.6. Geographic Qualification

If the return value in the main criterion includes whitespace, the remaining information in the field is used as a qualifier for the subsidiary shipping modes. This can be used to create geographic qualifications for shipping, as in:

```
upsg    UPS Ground    weight [value state]    0      0      e No items selected
upsg    UPS Ground    AK HI                   0      150    u Ground [value zip] 12.00
upsg    UPS Ground                                0      150    u Ground [value zip] 3.00
```

If `upsg` is the mode selected, the value of the user session variable `state` is examined to see if it matches the geographic qualification on a whole-word boundary. If it is `AK` or `HI`, UPS Ground with an adder of 12 will be selected. If it "falls through," UPS Ground with an adder of 3 will be selected.

6.7. Handling Charges

Additional handling charges can be defined in the shipping file by setting the form variable `mv_handling` to a space, comma, or null-separated set of valid shipping modes. The lookup and charges are created in the same fashion, and the additional charges are added to the order. (The user is responsible for displaying the charge on the order report or receipt with a `[shipping handling]` tag, or the like.) All of the shipping modes found in `mv_handling` will be applied. If multiple instances are found on a form, the

accordingly null-separated values will all be applied. NOTE: This should not be done in an item-list unless the multiple setting of the variables is accounted for.

To only process a handling charge once, do the following:

```
[item-list]
[if-item-field very_heavy]
[perl values]
    return '' if $Values->{mv_handling} =~ /very_heavy/;
    return "<INPUT TYPE=hidden NAME=mv_handling VALUE=very_heavy>";
[/perl]
[/if-item-field]
[/item-list]
```

A non-blank/non-zero value in the database field will trigger Perl code which will only set `mv_handling` once.

6.8. Default Shipping Mode

If a default shipping mode other than `default` is desired, enter it into the `DefaultShipping` directive:

```
DefaultShipping    upsg
```

This will make the entry on the order form checked by default when the user starts the order process, if it is put in the form:

```
<INPUT TYPE=RADIO NAME=mv_shipmode VALUE=upsg [checked mv_shipmode upsg]>
```

To force a choice by the user, make `mv_shipmode` a required form variable (with `RequiredFields` or in an order profile) and set `DefaultShipping` to zero.

7. User Database

Interchange has a user database function which allows customers to save any pertinent values from their session. It also allows the setting of database or file access control lists for use in controlling access to pages and databases on a user-by-user basis.

The database field names in the user database correspond with the form variable names in the user session. If there is a column named `address`, when the user logs in the contents of that field will be placed in the form variable `address`, and will be available for display with `[value address]`. Similarly, the database value is available with `[data table=userdb column=address key=username]`.

The ASCII file for the database will not reflect changes unless the file is exported with `[tag export userdb] [/tag]`. It is not advisable to edit the ASCII file, as it will overwrite the real data that is in the DBM table. User logins and changes would be lost. Note: This would not happen with SQL, but editing the ASCII file would have no effect. It is recommended that the `NoImport` configuration directive be set accordingly.

The field names to be used are not set in concrete. They may be changed with options. Fields may be added or subtracted at any time. Most users will choose to keep the default demo fields for simplicity sake, as they cover most common needs. As distributed in the demo, the fields are:

```
code
accounts
acl
address
address_book
b_address
b_city
b_country
b_name
b_nickname
b_phone
b_state
b_zip
carts
city
country
db_acl
email
email_copy
fax
fax_order
file_acl
mv_credit_card_exp_month
mv_credit_card_exp_year
mv_credit_card_info
mv_credit_card_type
mv_shipmode
name
order_numbers
p_nickname
password
phone_day
phone_night
preferences
s_nickname
```

```
state
time
zip
```

A few of those fields are special in naming, though all can be changed via an option. A couple of the fields are reserved for Interchange's use.

Note: If not running with PGP or other encryption for credit card numbers, which is never recommended, it is important that the mv_credit_card_info field be removed from the database.

The special database fields are:

accounts	Storage for billing accounts book
address_book	Storage for shipping address book
b_nickname	Nickname of current billing account
carts	Storage for shopping carts
p_nickname	Nickname for current preferences
preferences	Storage for preferences
s_nickname	Nickname for current shipping address
db_acl	Storage for database access control lists
file_acl	Storage for file access control lists
acl	Storage for simple integrated access control

If not defined, the corresponding capability is not available.

Note: The fields accounts, address_book, carts, and preferences should be defined as a BLOB type, if using SQL. This is also suggested for the acl fields if those lists could be large.

Reserved fields include:

code	The username (key for the database)
password	Password storage
time	Last time of login

7.1. The [userdb ...] Tag

Interchange provides a [userdb ...] tag to access the UserDB functions.

```
[userdb
  function=function_name
  username="username"*
  assign_username=1
  username_mask=REGEX*
  password="password"*
  verify="password"*
  oldpass="old password"*
  crypt="1|0"*
  shipping="fields for shipping save"
  billing="fields for billing save"
  preferences="fields for preferences save"
  ignore_case="1|0"*
```


Interchange Databases

```
force_lower=1
param1=value*
param2=value*
...
]
```

* Optional

It is normally called in an mv_click or mv_check setting, as in:

```
[set Login]
mv_todo=return
mv_nextpage=welcome
[userdb function=login]
[/set]

<FORM ACTION="[process-target]" METHOD=POST>
<INPUT TYPE=hidden NAME=mv_click VALUE=Login>
Username <INPUT NAME=mv_username SIZE=10>
Password <INPUT NAME=mv_password SIZE=10>
</FORM>
```

There are several global parameters that apply to any use of the userdb functions. Most importantly, by default, the database table is set to be userdb. If another table name must be used, include a database=table parameter with any call to userdb. The global parameters (default in parens):

database	Sets user database table (userdb)
show	Show the return value of certain functions or the error message, if any (0)
force_lower	Force possibly upper-case database fields to lower case session variable names (0)
billing	Set the billing fields (see Accounts)
shipping	Set the shipping fields (see Address Book)
preferences	Set the preferences fields (see Preferences)
bill_field	Set field name for accounts (accounts)
addr_field	Set field name for address book (address_book)
pref_field	Set field name for preferences (preferences)
cart_field	Set field name for cart storage (carts)
pass_field	Set field name for password (password)
time_field	Set field for storing last login time (time)
expire_field	Set field for expiration date (expire_date)
acl	Set field for simple access control storage (acl)
file_acl	Set field for file access control storage (file_acl)
db_acl	Set field for database access control storage (db_acl)

By default the system crypt() call will be used to compare the password. This is best for security, but the passwords in the user database will not be human readable.

If no critical information is kept and Interchange administration is not done via the UserDB capability, use the UserDB directive (described below) to set encryption off by default:

```
UserDB    default    crypt    0
```

Encryption can still be set on by passing crypt=1 with any call to a new_account, change_pass, or login call.

7.2. Setting Defaults with the UserDB Directive

The UserDB directive provides a way to set defaults for the user database. For example, to save and recall the scratch variable `tickets` in the user database instead of the form variable `tickets`, set:

```
UserDB    default    scratch    tickets
```

That makes every call to `[userdb function=login]` equivalent to `[userdb function=login scratch=tickets]`.

To override that default for one call only, use `[userdb function=login scratch="passes"]`.

To log failed access authorizations, set the UserDB profile parameter `log_failed` true:

```
UserDB    default    log_failed 1
```

To disable logging of failed access authorizations (the default), set the UserDB profile parameter `log_failed` to 0:

```
UserDB    default    log_failed 0
```

The UserDB directive uses the same key–value pair settings as the `Locale` and `Route` directives. If there are more than one set of defaults, set them in a hash structure:

```
UserDB    crypt_case    <<EOF
{
    'scratch'           => 'tickets',
    'crypt'             => '1',
    'ignore_case'       => '0',
}
EOF

UserDB    default    <<EOF
{
    'scratch'           => 'tickets',
    'crypt'             => '1',
    'ignore_case'       => '1',
}
EOF
```

Note: The usual here–document caveats apply. The "EOF" must be on a line by itself with no leading/trailing whitespace.

The last one to be set becomes the default.

The option `profile` selects the set to use. For usernames and passwords to be case sensitive with no encryption, pass this call:

```
[userdb function=new_account profile=case_crypt]
```

The username and password will be stored as typed in, and the password will be encrypted in the database.

7.3. User Database Functions

The user database features are implemented as a series of functions attached to the `userdb` tag. The functions are:

login

Active parameters: `username`, `password`, `crypt`, `pass_field`, `ignore_case`

Log in to Interchange. By default, the username is contained in the form variable `mv_username` and the password in `mv_password`. If the login is successful, the session value `username ([data session username])` will be set to the user name.

This will recall the values of all non-special fields in the user database and place them in their corresponding user form variables.

The `CookieLogin` directive (`catalog.cfg`) allows users to save their username/password in a cookie.

Expiration time is set by `SaveExpire`, renewed every time they log in. To cause the cookie to be generated originally, the form variable `mv_cookie_password` or `mv_cookie_username` must be set in the login form. The former causes both username and password to be saved, the latter just the username.

logout

Log out of Interchange. No additional parameters are needed.

new_account

Active parameters: `username`, `password`, `verify`, `assign_username`, `username_mask`, `ignore_case`

Create a new account. It requires the `username`, `password`, and `verify` parameters, which are by default contained in the form variables `mv_username`, `mv_password`, `mv_verify` respectively.

If the `assign_username` parameter is set, `UserDB` will assign a sequential username. The `counter` parameter can be used to set the filename (must be absolute), or the default of `CATALOG_DIR/etc/username.counter` can be accepted. The first username will be "U0001" if the counter doesn't exist already.

The `ignore_case` parameter forces the username and password to lower case in the database, in effect rendering the username and password case-insensitive.

If `username_mask` is set to a valid Perl regular expression (without the surrounding `/`), then any username containing a matching string will not be allowed for use. For example, to screen out order numbers from being used by a random user:

```
[userdb function=new_account
      username_mask="^[A-Z]*[0-9]"
]
```

The `CookieLogin` directive (`catalog.cfg`) allows users to save their username/password in a cookie.

Expiration time is set by `SaveExpire`, renewed every time they log in. To cause the cookie to be generated originally, the form variable `mv_cookie_password` or `mv_cookie_username` must be set in the login form. The former causes both username and password to be saved, the latter just the username.

To automatically create an account for every order, set the following in the `OrderReport` file:

```
[userdb function=new_account
      username="[value mv_order_number]"
      password="[value zip]"
      verify="[value zip]"
      database="orders"
```

]

This would be coupled with a login form that asks for order number and zip code, thereupon allowing the display of the contents of a transaction database with (presumably updated) order status information or a shipping company tracking number.

change_pass

Active parameters: username, password, verify, oldpass

Change the password on the currently logged-in account. It requires the username, password, verify, and oldpass parameters, which are by default contained in the form variables mv_username, mv_password, mv_verify, mv_password_old respectively.

set_shipping

Active parameters: nickname, shipping, ship_field

Place an entry in the shipping Address book. For example:

```
[userdb function=set_shipping nickname=Dad]
```

See Address Book below.

get_shipping

Active parameters: nickname, shipping, ship_field

Recall an entry from the shipping Address book. For example:

```
[userdb function=get_shipping nickname=Dad]
```

See Address Book below.

get_shipping_names

Active parameters: ship_field

Gets the names of shipping address book entries and places them in the variable address_book. By default, it does not return the values. To have the values returned, set the parameter show to 1, as in:

```
[set name=shipping_nicknames  
  interpolate=1]  
[userdb function=get_shipping_names show=1]  
[/set]
```

set_billing

Active parameters: nickname, billing, bill_field

Place an entry in the billing accounts book. For example:

```
[userdb function=set_billing nickname=discover]
```

See Accounts Book below.

get_billing

Active parameters: nickname, billing, bill_field

Recall an entry from the billing accounts book. For example:

```
[userdb function=get_billing nickname=visa]
```

See Accounts Book below.

save

Saves all non-special form values that have columns in the user database.

set_cart

Save the contents of a shopping cart.

```
[userdb function=set_cart nickname=christmas]
```

See Carts below.

get_cart

Active parameters: nickname, carts_field, target

Recall a saved shopping cart.

```
[userdb function=get_cart nickname=mom_birthday]
```

Setting target saves to a different shopping cart than the default main cart. The carts_field controls the database field used for storage.

set_acl

Active parameters: location, acl_field, delete

Set a simple acl. For example:

```
[userdb function=set_acl location=cartcfg/editcart]
```

This allows the current user to access the page "cartcfg/editcart" if it is access-protected.

To delete access, do:

```
[userdb function=set_acl location=cartcfg/editcart delete=1]
```

To display the setting at the same time as setting, use the show attribute:

```
[userdb function=set_acl location=cartcf/editcart show=1]
```

check_acl

Active parameters: location, acl_field

Checks the simple access control listing for a location, returning 1 if allowed and the empty string if not allowed.

```
[if type=explicit
```

Interchange Databases

```
compare="[userdb
        function=check_acl
        location=cartcfg/editcart]"
]
[page cartcfg/editcart]Edit your cart configuration[/page]
[/if]
```

set_file_acl, set_db_acl

Active parameters: location, mode, db_acl_field, file_acl_field, delete

Sets a complex access control value. Takes the form:

```
[userdb function=set_file_acl
        mode=rw
        location=products/inventory.txt]
```

where mode is any value to be checked with `check_file_acl`. As with the simple ACL, use `delete=1` to delete the location entirely.

check_file_acl, check_db_acl

Active parameters: location, mode, db_acl_field, file_acl_field

Checks a complex access control value and returns a true/false (1/0) value. Takes the form:

```
[userdb function=check_db_acl
        mode=w
        location=inventory]
```

where mode is any value to be checked with `check_file_acl`. It will return true, if the mode string is contained within the entry for that location. For example:

```
[if type=explicit
  compare="[userdb
            function=check_db_acl
            mode=w
            location=inventory]"
]
[userdb function=set_acl location=cartcfg/edit_inventory]
[page cartcfg/edit_inventory]You may edit the inventory database[/page]
[else]
[userdb function=set_acl location=cartcfg/edit_inventory delete=1]
Sorry, you can't edit inventory.
[/if]
```

7.4. Address Book

Address_book is a shipping address book. The shipping address book saves information relevant to shipping the order. In its simplest form, this can be the only address book needed. By default these form values are included:

```
s_nickname
name
fname
lname
address
address1
```

```
address2
address3
city
state
zip
country
phone_day
mv_shipmode
```

The first field is always the name of the form variable that contains the key for the entry. The values are saved with the `[userdb function=set_shipping]` tag call, and are recalled with `[userdb function=get_shipping]`. A list of the keys available is kept in the form value `address_book`, suitable for iteration in an HTML select box or in a set of links.

To get the names of the addresses, use the `get_shipping_names` function:

```
[userdb function=get_shipping_names]
```

By default, they are placed in the variable `address_book`. Here is a little snippet that builds a select box:

```
<FORM ACTION="[process-target]" METHOD=POST>
[userdb function=get_shipping_names]
[if value address_book]
<SELECT NAME="s_nickname">
[loop arg="[value address_book]" <OPTION> [loop-code] [/loop]
</SELECT>
<INPUT TYPE=submit NAME=mv_check VALUE="Recall Shipping">
</FORM>
```

The same principle works with accounts, carts, and preferences.

To restore a cart based on the above, put in an `mv_check` routine:

```
[set Recall Shipping]
mv_todo=return
mv_nextpage=ord/basket
[userdb function=get_shipping nickname="[value s_nickname]"]
[/set]
```

When the `mv_check` variable is encountered, the contents of the scratch variable `Recall Shipping` are processed and the shipping address information inserted into the user form values. This is destructive of any current values of those user session variables, of course.

To change the fields that are recalled or saved, use the `shipping` parameter:

```
[userdb function=get_shipping
    nickname=city_and_state
    shipping="city state"]
```

Only the values of the `city` and `state` variables will be replaced.

7.5. Accounts Book

The accounts book saves information relevant to billing the order. By default these form values are included:

```
b_nickname
b_name
b_fname
b_lname
b_address
b_address1
b_address2
b_address3
b_city
b_state
b_zip
b_country
b_phone
purchase_order
mv_credit_card_type
mv_credit_card_exp_month
mv_credit_card_exp_year
mv_credit_card_info
```

The values are saved with the `[userdb function=set_billing]` tag call, and are recalled with `[userdb function=get_billing]`. A list of the keys available is kept in the form value accounts, suitable for iteration in an HTML select box or in a set of links.

7.6. Preferences

Preferences are miscellaneous session information. They include, by default, the following fields:

```
email
fax
phone_night
fax_order
email_copy
```

The field `p_nickname` acts as a key to select the preference set. To change the values that are included with the preferences parameter:

```
[userdb function=set_preferences
  preferences="email_copy email fax_order fax"]
```

or in `catalog.cfg`:

```
UserDB default preferences "mail_list email fax_order music_genre"
```

7.7. Carts

The contents of shopping carts may be saved or recalled in much the same fashion. See the Simple demo application `ord/basket.html` page for an example.

7.8. Controlling Page Access With UserDB

Interchange can implement a simple access control scheme with the user database. Controlled pages must reside in a directory which has a file named `.access` that is zero bytes in length. (If it is more than 0 bytes, only the RemoteUser or MasterHost may access files in that directory.)

Interchange Databases

Set the following variables in `catalog.cfg`:

```
Variable    MV_USERDB_ACL_TABLE    userdb
Variable    MV_USERDB_ACL_COLUMN    acl
```

The `MV_USERDB_ACL_TABLE` is the table which controls access, and likewise the `MV_USERDB_ACL_COLUMN` names the column in that database which will be checked for authorization.

The database entry should contain the complete Interchange-style page name of the page to be allowed. It will not match substrings.

For example, if the user `flycat` followed this link:

```
<A HREF="[area cartcfg/master_edit]">Edit</A>
```

Access would be allowed if the contents of the `userdb` were:

```
code    acl
flycat  cartcfg/master_edit
```

and disallowed if it were:

```
code    acl
flycat  cartcfg/master_editor
```

Access can be enabled with:

```
[userdb function=set_acl location="cartcfg/master_edit"]
```

Access can be disallowed with:

```
[userdb function=set_acl
      delete=1
      location="cartcfg/master_edit"]
```

Of course, a pre-existing database with the ACL values will work as well. It need not be in the UserDB setup.

8. Back Office UI

8.1. [display] tag and mv_metadata

The Interchange back office UI uses the mv_metadata table to discover formatting information for field, table, and view display. The information is kept in fields in the mv_metadata table, and is used to select the display, the HTML input type, the size (height and width where appropriate), label, help text, additional help URL, and default value display.

It works in conjunction with the [display ...] usertag defined in the Interchange UI as well as in specific pages in the UI. The [display] tag has this syntax:

```
[display table=tablename column=fieldname key=key arbitrary=tag filter=op ...]
```

In the simplest use, the formatting information for a table form field is called with:

```
[display table=products column=category key="os28007"]
```

The mv_metadata table is scanned for the following keys:

```
products::category::os28007
products::category
```

If a row is found with one of those keys, then the information in the row is used to set the display widget. If no row is found, an INPUT TYPE=TEXT widget is displayed. If the data is all digits, a size of 8 is used, otherwise the size is 60.

If the following row were found (not all fields shown, would be tab-separated in the actual data):

code	type	width	height	label	options
products::category	text	20		Category	

Then an input <INPUT TYPE=text SIZE=20 VALUE="*category*"> with a field label of *Category* would be output.

If the following row were found:

code	type	width	height	label	options
products::category	select			Category	=none, product=Hardware

Then the following would be output:

```
<SELECT NAME=category>
<OPTION VALUE=" ">none
<OPTION VALUE="product">Hardware
</SELECT>
```

The standard widget types are:

text

The default. Uses the fields:

width size of input box

textarea

Format a `<TEXTAREA>` `</TEXTAREA>` pair. Uses the fields:

width COLS for textarea
height ROWS for textarea

select

Format a `<SELECT>` `</SELECT>` pair with appropriate options. Uses the fields:

height SIZE for select
default Default for SELECTED
options Options for a fixed list (or prepended to a lookup)
lookup signals a lookup (used as field name if "field" empty)
field field to look up possible values in
db table to look up in if not current table
lookup_exclude regular expression to exclude certain values from lookup

9. Standard Database Dictionary

You can alter any of the standard databases to suit your needs, add new databases, or remove unneeded ones. But the following dictionary lists each table and each of its fields, and explains its purpose.

9.1. 2ndDayAir.csv

Shipping table

9.2. 450.csv

Shipping table

9.3. Ground.csv

Shipping table

9.4. NextDayAir.csv

Shipping table

9.5. access.asc

Admin access table

```
username
password
name
last_login
super
yes_tables
no_tables
upload
acl
export
edit
pages
files
config
reconfig
groups
meta

no_functions
    Used From: none

yes_functions
    Used From: dist/lib/UI/pages/admin/access_permissions.html

table_control
    Used From: dist/lib/UI/Primitive.pm
               dist/lib/UI/pages/admin/special/key_violation.html
```

```
dist/lib/UI/usertag/if_mm
```

```
personal_css
```

```
Used From: dist/lib/UI/pages/admin/preferences.html
```

```
Used in the admin screens to make personal changes to the admin  
presentation, by creating your own personal CSS, appears to be used  
currently only in the preferences screen.
```

9.6. affiliate.txt

```
affiliate  
name  
    Affiliate Name  
campaigns  
coupon_amount  
join_date  
    Join date  
url  
    URL (Default URL to redirect to)  
timeout  
    Timeout delay (in seconds, 0 to disable)  
active  
password  
image
```

9.7. area.txt

```
code  
sel  
name  
which_page  
sort  
display_type  
image  
image_prop  
banner_image  
banner_text  
link_type  
    none = No link  
    external = External link (http://...)  
    internal = Interchange page  
    simple = Simple search  
    complex = Complex search  
url  
tab  
page  
search  
selector  
link_template
```

9.8. banner.txt

```
code  
category  
weight  
rotate  
banner
```

9.9. cat.txt

```

code
sel
name
which_page
sort
display_type
    name = Name
    url = URL only
    icon = Icon and name
    image = Image
image
image_prop
banner_image
banner_text
link_type
    Type of link:
        none = No link
        external = External link (http://...)
        internal = Interchange page
        simple = Simple search
        complex = Complex search
url
tab
page
search
selector
link_template

```

9.10. component.txt

```

code
group
name
width
height
pieces
label
banner
help
help_url
filter
controls
Variable

```

9.11. country.txt

```

code
sorder
region
selector
shipmodes
name

```

9.12. downloadable.txt

```
sku
dl_location
dl_type
```

9.13. files.txt

9.14. gift_certs.txt

```
code
username
order_date
original_amount
redeemed_amount
available_amount
passcode
active
redeemed
update_date
```

9.15. icmenu.txt

```
code
mgroup
msort
next_line
indicator
exclude_on
depends_on
page
form
name
super
inactive
special
help_name
```

9.16. inventory.txt

```
sku
    Quantity info
quantity
stock_message
    Out of stock message:
        In stock
        Ships in 3-5 days
        Ships in 4-6 weeks
        Special order
account
    Accounting info
    Sales account
cogs_account
```


9.17. locale.txt

```
code
en_US
de_DE
fr_FR
```

9.18. merchandising.txt

```
sku
featured
banner_text
banner_image
blurb_begin
blurb_end
    Closer (end text for feature display)
timed_promotion
start_date
    Start date
finish_date
upsell_to
    Cross-sell SKUs
cross_sell
cross_category
others_bought
times_ordered
```

9.19. mv_metadata.asc

```
code
    Table::Column to be operated on.
    Database table
type
    Widget type (Select the basic display type for the field)
        textarea = Textarea
        text = Text Entry (default)
        select = Select Box
        yesno = Yes/No (Yes=1)
        noyes = No/Yes (No=1)
        multiple = Multiple Select
        combo = Combo Select
        reverse_combo = Reverse Combo
        move_combo = Combo move
        display = Text of option
        hidden_text = Hidden(show text)
        radio = Radio box
        radio_nbsp = Radio (nbsp)
        checkbox = Checkbox
        check_nbsp = Checkbox (nbsp)
        imagedir = Image listing
        imagehelper = Image upload
        date = Date selector
        value = Value
        option_format = Option formatter
        show = Show all options
width
    Width (SIZE for TEXT, COLS for TEXTAREA, Label limit for SELECT)
height
```

Interchange Databases

Height (SIZE for SELECT, ROWS for TEXTAREA)
field
Field for lookup (can be two comma separated fields, in which case second is used as the label text. Both must be in the same table.)
db
name
Variable name (normally left empty, changes variable name to send in form)
outboard
Select directory for image listing widget
options
options in the format <blockquote>value=label*</blockquote>
attribute
Column name (Do not set this.)
label
help
Help (displays at top of page)
lookup
Lookup select (Whether lookup is performed to get options for a select type. If nothing is in the field, then used as the name of the field to lookup in. Use lookup table if you want to look up in a different table.)
filter
Filters (Filters which can transform or constrain your data. Some widgets require filters.)
help_url
Help URL (links below help text)
A URL which will provide more help
pre_filter
lookup_exclude
ADVANCED: regular expression that excludes certain keys from the lookup
prepend
append
Append HTML (HTML to be appended to the widget. Will substitute in the macros `_UI_TABLE_`, `_UI_COLUMN_`, `_UI_KEY_`, and `_UI_VALUE_`, and will resolve relative links with absolute links.)
display_filter

9.20. options.txt

code
o_master
Master item (Always included when the base SKU is equal to this.)
sku
Unique SKU (Associated item)
o_group
Option Group (scanned to see if it applies (or doesn't apply) to this product)
o_sort
phantom
Phantom? (Whether a phantom for structuring)
o_enable
Follow? (Enable for next level) Sub-items
o_matrix
Matrix options (Matrix options allow you to maintain multiple option sets with inventory on each combination)
o_modular
Modular Options (Modular options allow you to attach multiple SKUs to the same item, possibly with attached options of their own. Very complex but you can do most anything.)
o_default

Default? (Yes if the default selection for the group)

o_label
Short name for option display

o_value
Possible Values (In Interchange option format: VALUE1=Label 1,
VALUE2=Label 2 *=default selection)

o_widget

o_footer

o_header

o_height
Height of widget (if applicable)

o_width
Width of widget

description
Option/Variant description (for description in display)

price
Price (Price of this option/variant)

wholesale
Dealer price

differential

weight

volume
Volume (if different, mostly for matrix/modular)

mv_shipmode

o_exclude
Exclude (Only for modular options. Lists the option groups to exclude
once the include has been done. Takes the form of a number of wildcard
atoms.)

o_include
Include (Only for modular options. Lists the option groups to include
with your item. Takes the form of a number of wildcard atoms.)

9.21. order_returns.txt

code
order_number
session
username
rma_number
nitems
total
return_date
update_date

9.22. orderline.txt

code
store_id
order_number
session
username
shipmode
sku
quantity
price
subtotal
shipping
taxable
mv_mi

```
mv_si
size
color
options
order_date
update_date
status
    pending = Pending
    shipped = Shipped
    backorder = Back ordered
    credit = Waiting for credit check
    canceled = Cancelled
parent
affiliate
campaign
description
mv_mp
```

9.23. pricing.txt

```
sku
price_group
q2
q5
q10
q25
q100
```

9.24. products.txt

```
sku
description
    Short Description
title
    Title
template_page
comment
    Detailed Description
thumb
    Thumb
image
    Image
price
wholesale
    Dealer Price
prod_group
category
    Category (Enter in box for new category.)
nontaxable
weight
    Weight in pounds
size
color
gift_cert
    Gift certificate handling? (Yes if price should appear to be quantity)
related
featured
download
dl_type
```

dl_location
inactive
url

9.25. route.txt

code
attach
continue
commit
commit_tables
counter
credit_card
cyber_mode
email
empty
encrypt
encrypt_program
errors_to
increment
inline_profile
individual_track
individual_track_ext
partial
pgp_cc_key
pgp_key
profile
receipt
reply
report
rollback
rollback_tables
supplant
track

9.26. saletax.asc

9.27. shipping.asc

Shipping methods table

9.28. state.txt

State/territory/county information

code
sorder
country
state
name
tax
postcode
shipmodes
tax_name

9.29. transactions.txt

Order table, one entry per order, assoc with orderline

```

code
store_id
order_number
session
username
shipmode
nitems
subtotal
shipping
handling
salestax
total_cost
fname
lname
    Last Name
company
address1
address2
    Address line 2
city
state
zip
country
phone_day
    Daytime Phone
phone_night
    Home Phone
fax
email
b_fname
b_lname
    Billing Last Name
b_company
b_address1
b_address2
    Billing Address Line 2
b_city
b_state
    Billing State
b_zip
    Billing Postcode
b_country
    Billing Country
b_phone
order_date
order_ymd
order_wday
payment_method
po_number
avs
order_id
update_date
status
affiliate
campaign
parent
archived

```

deleted
complete
comments

9.30. userdb.txt

Customer database

```

username
password
acl
mod_time
s_nickname
company
fname
lname
address1
address2
address3
city
state
zip
    Postcode
country
    Country
phone_day
mv_shipmode
b_nickname
b_fname
b_lname
b_address1
b_address2
b_address3
b_city
b_state
b_zip
b_country
b_phone
    Billing Phone
mv_credit_card_type
mv_credit_card_exp_month
mv_credit_card_exp_year
p_nickname
email
fax
phone_night
fax_order
    Payment method:
        (none) = Credit Card
        1 = Fax or Mail
        2 = Purchase order
        3 = COD
address_book
accounts
preferences
carts
owner
file_acl
db_acl
order_numbers

```

```
email_copy
mail_list
    Mailing lists the customer has joined:
        offer = Special offers
        newsletter = Newsletter
        alert = Alerts and Recalls
        upgrade = Upgrades
project_id
account_id
order_dest
credit_limit
inactive
dealer
    Dealer:
        (none) = No
        1 = Yes
b_company
feedback
???
```

9.31. variable.txt

Configuration database

```
code
    Variable name
Variable
pref_group
    Preferences area
```


10. Frequently Asked Questions

10.1. Does Interchange require an SQL database?

No. Interchange does not require an external SQL database. If you have a small database with no particular desire to integrate your own tool set, you may be more comfortable using Interchange's internal database.

Bear in mind that the order management functions of Interchange will be slow and not as robust without SQL. SQL is strongly recommended for at least these three tables:

```
orderline
transactions
userdb
```

10.2. I can't get SQL to work: Undefined subroutine &Vend::Table::DBI::create ...

This probably means one of the following:

No SQL database.

Interchange doesn't include a SQL database. You must select one and install it.

No DBI.

You must install Perl's DBI module before using Interchange with SQL. You can see where to get it at <http://www.cpan.org>, or try:

```
perl -MCPAN -e 'install DBI'
```

No DBD.

You must install the specific Perl DBD module for your database before using Interchange with SQL. You can see where to get it at <http://www.cpan.org>, or try:

```
perl -MCPAN -e 'install DBD::XXXXX'
```

where XXXX is the name of your module. Some of them are:

```
Adabas
DB2
Informix
Ingres
ODBC
Oracle
Pg
Solid
Sybase
Unify
XBase
mSQL
mysql
```

If you can't make this script run without error:

```
use DBI;  
use DBD: :XXXXX;
```

Then you don't have one of the above, and Interchange will never run a SQL type.

I don't like the column types that Interchange defines!

They can be changed. See the `foundation/dbconf/mysql` directory for some examples under MySQL.

I change the ASCII file, but the table is not updated. Why?

Interchange writes an empty file `TABLE.sql` (where `TABLE` is the name of the table). When this is present, Interchange will never update the table from disk.

Also, if you have changed the field names in the file, you must restart the catalog (Apply Changes) before they will be picked up.

Why do I even need an ASCII file?

Interchange wants some source for column names initially. If you don't want to have one, just create a `TABLENAME.sql` file in the `products` directory. For example, if you have this:

```
Database products products.txt dbi:mysql:test_minivend
```

Then create a file `products/products.sql`.
\For:

```
Database pricing pricing.txt dbi:mysql:test_minivend
```

Create a file `products/pricing.sql`.

Interchange overwrites my predefined table!

Yes, it will if you don't create a file called `TABLENAME.sql`, where `TABLENAME` is the name of the Interchange table. If you want this to happen by default, then set `NoImport TABLENAME`.

10.3. How can I use Interchange with Microsoft Access?

Though Interchange has ODBC capability, the Microsoft Access ODBC driver is not a network driver. You cannot access it on a PC from your ISP or UNIX system.

However, you can turn it around. Once you have created a MySQL or other SQL database on the UNIX machine, you may then obtain the Windows ODBC driver for the database (MySQL has a package called `myODBC`) and use the UNIX database as a data source for your PC-based database program.

Here is a quick procedure that might get you started:

- Get MySQL from:
<http://www.mysql.com/>

Interchange Databases

Install it on your UNIX box. On LINUX, it is as easy as getting the RPM distribution:

```
http://www.mysql.com/rpm/
```

You install it by typing, as root, `rpm -i mysql-3.XX.XX.rpm`. If you are not root, you will have to build the source distribution.

- To avoid permissions problems for your testing, stop the MySQL daemon and allow global read-write access with:

```
mysqladmin shutdown  
safe_mysqld --skip-grant-tables &
```

Obviously, you will want to study MySQL permissions and set up some security pretty quickly. It has excellent capability in that area, and the FAQ will help you get over the hurdles.

- Set up a database for testing on the UNIX machine:

```
mysqladmin create test_odbc  
mysql test_odbc
```

Make an SQL query to set up a table, for example:

```
mysql> create table test_me ( code char(20), testdata char(20) );  
Query OK, 0 rows affected (0.29 sec)  
  
mysql> insert into test_me VALUES ('key1', 'data1');  
Query OK, 1 rows affected (0.00 sec)  
  
mysql> insert into test_me VALUES ('key2', 'data2');  
Query OK, 1 rows affected (0.00 sec)  
  
mysql>
```

- Get and install myODBC, also from the MySQL site:

```
http://www.mysql.com/
```

You install this package on your Windows 95 or NT box. It is a simple setup.exe process which leads you to the control panel for setting up an ODBC data source. Set up a data source named `test_odbc` that points to the database `test_odbc` on the UNIX box. You will need to know the host name and the port (usually 3306).

- With Microsoft Access, you can then open a blank database and select: File/Get External Data/Link Tables. Select File Type of 'ODBC databases' and the proper data source, and you should have access to the database residing on the UNIX side.

11. Interchange Database Usertags

11.1. Data

Named Parameters: [data table=db_table column=column_name key=key
filter=`uc|lc|name|namecase|no_white|etc.*` append=1* value=`value to set to`* increment=1*]

Positional parameters: [data db_table column key]

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: no

Called Routine:

ASP/perl tag calls:

```
$Tag->data(  
    {  
        table => VALUE,  
        field => VALUE,  
        key => VALUE,  
    }  
)
```

OR

```
$Tag->data($table, $field, $key, $ATTRHASH);
```

Attribute aliases:

```
base ==> table  
code ==> key  
col ==> field  
column ==> field  
database ==> table  
name ==> field  
row ==> key
```

Returns the value of the field in a database table, or (DEPRECATED) from the session namespace. If the optional value is supplied, the entry will be changed to that value. If the option increment* is present, the field will be automatically incremented with the value in value. Use negative numbers in value to decrement. The append attribute causes the value to be appended. The filter attribute is a set of Interchange filters that are applied to the data 1) after it is read; or 2) before it is placed in the table.

If a DBM-based database is to be modified, it must be flagged writable on the page calling the write tag. Use [tag flag write]products[/tag] to mark the products database writable, for example. This must be done before ANY access to that table.

DEPRECATED BEHAVIOR: (replace with session tag). In addition, the [data ...] tag can access a number of elements in the Interchange session database:

accesses	Accesses within the last 30 seconds
arg	The argument passed in a [page ...] or [area ...] tag
browser	The user browser string
cybercash_error	Error from last CyberCash operation
cybercash_result	Hash of results from CyberCash (access with usertag)
host	Interchange's idea of the host (modified by DomainTail)

Interchange Databases

last_error	The last error from the error logging
last_url	The current Interchange path_info
logged_in	Whether the user is logged in (add-on UserDB feature)
pageCount	Number of unique URLs generated
prev_url	The previous path_info
referer	HTTP_REFERER string
ship_message	The last error messages from shipping
source	Source of original entry to Interchange
time	Time (seconds since Jan 1, 1970) of last access
user	The REMOTE_USER string
username	User name logged in as (UserDB feature)

Note: Databases will hide session values, so don't name a database `session`. or you won't be able to use the [data ...] tag to read them. Case is sensitive, so in a pinch you could call the database ``Session", but it would be better not to use that name at all.

11.2. db_date

```
# [db-date table format]
#
# This tag returns the last-modified time of a database table,
# 'products' by default. Accepts a POSIX strftime value for
# date format; uses '%A %d %b %Y' by default.
#
UserTag db-date Order table format
UserTag db-date PosNumber 2
UserTag db-date Routine <<EOF
sub {
    my ($db, $format) = @_;
    my ($dbfile, $mtime);

    # use defaults if necessary
    $db = 'products' unless $db;
    $format = '%A %d %b %Y' unless $format;

    # build database file name
    $dbfile = $Vend::Cfg->{ProductDir} . '/'
        . $Vend::Cfg->{Database}{$db}{file};

    # get last modified time
    $mtime = (stat ($dbfile))[9];

    if (defined ($mtime)) {
        return POSIX::strftime($format, localtime($mtime));
    } else {
        logError ("Couldn't stat $dbfile: $!\n");
    }
}
EOF
```

11.3. search_region

Named Parameters: [search_region arg="arg"]

Positional Parameters: [search_region arg]

The attribute hash reference is passed after the parameters but before the container text argument. This may

mean that there are parameters not shown here.

Must pass named parameter `interpolate=1` to cause interpolation.

This is a container tag, i.e. `[search_region] FOO [/search_region]`. Nesting: NO

Invalidates cache: no

Called Routine:

ASP/perl tag calls:

```
$Tag->search_region(  
    {  
        arg => VALUE,  
    },  
    BODY  
)
```

OR

```
$Tag->search_region($arg, $ATTRHASH, $BODY);
```

Attribute aliases:

```
args ==> arg  
params ==> arg  
search ==> arg
```

